

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id **SAB Ideal Electric Generator**

Component Circulating Bearing

DIAGNOSIS

A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 6 microns in size) present in the oil. There is a trace of moisture present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oils additive package is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06147932		
Sample Date		Client Info		09 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	nnm	ASTM D5185m	>20	9		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	nnm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m	0	0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	0		
Lead	nnm	ASTM D5185m	>20	د د1		
Copper	nnm	ASTM D5185m	>20	2		
Tin	ppm	ASTM D5185m	>20	- 12		
Vanadium	nnm	ASTM D5185m	20	0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	nnm	ASTM D5185m	5	0		
Barium	nnm	ASTM D5185m	5	0		
Molybdenum	nnm	ASTM D5185m	5	0		
Manganese	nnm	ASTM D5185m	0	۰ د1		
Magnesium	ppm	ASTM D5185m	5	<1		
Calcium	ppm	ASTM D5185m	12	39		
Phosphorus	ppm	ASTM D5185m	400	7		
Zinc	ppm	ASTM D5185m	12	0		
Sulfur	mag	ASTM D5185m	650	56		
CONTAMINANTS		method	limit/base	current	history1	history2
Silioon	nnm	ACTM DE105m	. 15	-1		
Sodium	ppm	ASTM D5185m	>15	<1		
Botaccium	ppm	ASTM D5185m	> 20	< 1		
Water	٥ <u>/</u>		>20	0 170		
nom Water	⁷⁰	ASTM D6304	22	1709		
		mothod	limit/base	ourropt	biotonut	history?
	1200				mstory	nistory2
Particles >4µm		ASTM D7647	>10000	A 32912		
Particles >6µm		ASTM D7647	>2500	2169		
Particles >14µm		ASTM D7647	>160	54		
Particles >21µm		ASTM D7647	>40	1/		
Particles >38µm		ASTM D/647	>10	2		
Particles >/1µm		ASTM D/64/	>3	00/10/10		
Oil Cleanliness		15U 4406 (C)	>20/18/14	22/18/13		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.50	0.05		

Contact/Location: Jim Hudson - UCCORROC Page 1 of 2



OIL ANALYSIS REPORT











To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Test Package : IND 2 (Additional Tests: KF, PrtCount)

Certificate 12367

Laboratory

Sample No.

Lab Number

Contact/Location: Jim Hudson - UCCORROC

Page 2 of 2

Contact: Jim Hudson

T: (716)261-6637

F: (585)247-7268

jhudson@corrosion-products.com