




OIL ANALYSIS REPORT

Area
Watkins Block Truck Shop Omaha
 Machine Id
99 [Watkins Block Truck Shop Omaha]
 Component
Front Diesel Engine
 Fluid
PETRO CANADA DURON SHP 10W30 (38 QTS)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		SBP0007081	SBP0004681	SBP0000252
Sample Date	Client Info		09 Apr 2024	10 Jul 2023	16 Aug 2022
Machine Age	mls	Client Info	238584	226324	210725
Oil Age	mls	Client Info	12060	15451	30840
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	9	21	37
Chromium	ppm	ASTM D5185m >20	0	<1	<1
Nickel	ppm	ASTM D5185m >5	0	<1	<1
Titanium	ppm	ASTM D5185m >2	0	0	<1
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >20	2	5	6
Lead	ppm	ASTM D5185m >40	<1	1	4
Copper	ppm	ASTM D5185m >330	2	4	9
Tin	ppm	ASTM D5185m >15	<1	2	2
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	0	4	15
Barium	ppm	ASTM D5185m 0	0	0	0
Molybdenum	ppm	ASTM D5185m 50	52	56	8
Manganese	ppm	ASTM D5185m 0	<1	<1	1
Magnesium	ppm	ASTM D5185m 950	819	989	698
Calcium	ppm	ASTM D5185m 1050	1006	1210	1404
Phosphorus	ppm	ASTM D5185m 995	844	1032	741
Zinc	ppm	ASTM D5185m 1180	1015	1257	864
Sulfur	ppm	ASTM D5185m 2600	2865	3681	2820

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	4	7	13
Sodium	ppm	ASTM D5185m	6	6	14
Potassium	ppm	ASTM D5185m >20	0	3	4
Chlorine	ppm	ASTM D5185m	---	---	---

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	0.5	0.8	1.1
Nitration	Abs/cm	*ASTM D7624 >20	11.0	12.6	18.3
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.7	24.1	33.5

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	18.1	20.2	32.4
Base Number (BN)	mg KOH/g	ASTM D2896	5.1	5.6	3.4







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	10.9	11.1

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : SBP0007081
Lab Number : **06147994**
Unique Number : 10978072
Test Package : FLEET
Received : 12 Apr 2024
Tested : 15 Apr 2024
Diagnosed : 15 Apr 2024 - Wes Davis

Watkins Block Truck Shop Omaha - 60227
 14306 Giles Rd
 Omaha, NE
 US 68138

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)