


OIL ANALYSIS REPORT

BARRIER DEPARTMENT SAMPLES

LUFKIN/WELEX WEB 05 CC COATING-SARAN (S/N 341-37871)

Gearbox

TEXACO MEROPA 220 (15 GAL)



Sample Rating Trend



DIAGNOSIS

Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMA	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0913517	WC0806378	WC0757260
Sample Date		Client Info		14 Apr 2024	08 Oct 2023	04 Apr 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	NORMAL
CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	92	95	73
Chromium	ppm	ASTM D5185m	>15	<1	<1	<1
Nickel	ppm	ASTM D5185m	>15	<1	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	1	1	<1
	ppm	ASTM D5185m	>100	0	0	0
_	ppm	ASTM D5185m	>200	3	1	<1
Tin	ppm	ASTM D5185m	>25	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	3.2	<1	2	<1
Barium	ppm	ASTM D5185m	0.5	0	0	0
Molybdenum	ppm	ASTM D5185m	1.1	0	0	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	0.1	2	4	0
Calcium	ppm	ASTM D5185m	1.6	2	5	<1
Phosphorus	ppm	ASTM D5185m	159	289	280	294
	ppm	ASTM D5185m	0.5	9	6	10
Sulfur	ppm	ASTM D5185m	10342	9029	8510	9974
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	5	6	4
0 "		ASTM D5185m		5	4	2
	ppm	ASTM D5185m	>20	<1	<1	1
FLUID CLEANLINE	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647				33604
Particles >6µm		ASTM D7647	>5000			4597
Particles >14µm		ASTM D7647	>640			130
Particles >21µm		ASTM D7647	>160			29
Particles >38µm		ASTM D7647	>40			1
Particles >71µm		ASTM D7647	>10			0
Oil Cleanliness		ISO 4406 (c)	>/19/16			22/19/14
FLUID DEGRADAT	ION	method	limit/base	current	history1	history2
. LOID DEGITABAT	.0.1	motriou	mm/base	Odificiti	Thistory I	Thistory Z



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	▲ MODER	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	▲ MODER	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	219	215	215	213
SAMPLE IMAGES		method	limit/base	current	history1	history2





Color

Bottom













Certificate 12367

Laboratory

Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0913517 Lab Number : 06148703 Unique Number : 10978781

Received **Tested** Diagnosed

: 15 Apr 2024 : 17 Apr 2024

: 17 Apr 2024 - Don Baldridge

SEALED AIR CORP - CRYOVAC DIVISION 1301 WEST MAGNOLIA AVE IOWA PARK, TX

US 76367 Contact: KEVIN KETCHERSID

F: (940)592-2513

kevin.a.ketchersid@sealedair.com T: (940)592-2111

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Test Package : IND 2 (Additional Tests: PrtCount)

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)