

OIL ANALYSIS REPORT

Area ACS-46-5 [418290] ATLAS COPCO API629431 - THE PAIGE CO

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06148799		
Sample Date		Client Info		06 Apr 2024		
Machine Age	hrs	Client Info		26560		
Oil Age	hrs	Client Info		5952		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>5	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>15	0		
Lead	ppm	ASTM D5185m	>65	0		
Copper	ppm	ASTM D5185m	>65	0		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1.5	0		
Barium	ppm	ASTM D5185m	0	0		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m	0.3	0		
Magnesium	ppm	ASTM D5185m	0	0		
Calcium	ppm	ASTM D5185m	0	0		
Phosphorus	ppm	ASTM D5185m	406	2		
Zinc	ppm	ASTM D5185m	0	0		
Sulfur	ppm	ASTM D5185m	1283	4		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	<1		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.463	0.25		



OIL ANALYSIS REPORT

VISUAL





	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal		*Visual	NONE	NONE		
	Precipitate		*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris		*Visual	NONE	NONE		
	Sand/Dirt		*Visual	NONE	NONE		
Apr6/24 -	Appearance		*Visual	NORML	NORML		
Apré	Odor		*Visual	NORML	NORML		
	Emulsified Water		*Visual	>0.1	NEG		
	Free Water		*Visual	2011	NEG		
				line it //e e e e			
	FLUID PROPERT		method	limit/base	current	history1	history2
	Visc @ 40°C		ASTM D445		52.0		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Apr6/24 +	Color					no image	no image
	Bottom					no image	no image
	8 - iron						
	udd 2 0 4 4 2 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4			Apr6/24			
	6 4 2 0	ls		Apr6/24			
	Non-ferrous Meta	ls		Apr6/24	Acid Number		
	Non-ferrous Meta	ls		Apr6/24	Acid Number		
	Non-ferrous Meta	ls		Apr6/24			
	Non-ferrous Meta	ls		Apr6/24			
	Non-ferrous Meta	ls		Apr6/24			
	Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C	ls		0000 0000 0000 0000 0000 0000 0000 0000 0000	Base		
	Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C Abnomal Base Abnomal	ls		00.0 (0) 00.0 (
Laboratory Sample No. Lab Number Unique Number Tisticate L2367	Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C Solution Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta WearCheck USA - 50 UCH06148799 : 10978877		ved :15 d :16	Apr6/24 0000 Apr6/24 Apr6/24 0000 Apr6/24 Apr6/24 0000 Apr6/24 Apr	HIRMAT	C	

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ELVIN DIAZ - UCAIRCAR

F: (201)342-6241