

# **OIL ANALYSIS REPORT**

## Sample Rating Trend









Byron Center CAT 1 BYCM01BE

Biogas Engine

CHEVRON HDAX 9500 GAS ENGINE OIL 40 (--- GAL)

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil


## **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


CAMPI E INFORM	AATION	on a the series	Line is the con-		la la taran d	المستحدث المستحدث
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0877015	WC0640330	WC0877088
Sample Date		Client Info		12 Apr 2024	04 Apr 2024	25 Mar 2024
Machine Age	hrs	Client Info		87284	87096	86858
Oil Age	hrs	Client Info		243	54	645
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	SEVERE
CONTAMINATION	1	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method		NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>14	2	<1	6
Chromium	ppm	ASTM D5185m	>3	0	0	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>5	1	<1	3
Lead	ppm	ASTM D5185m	>8	0	0	0
Copper	ppm	ASTM D5185m	>5	<1	0	2
Tin	ppm	ASTM D5185m	>3	<1	<1	<u>4</u>
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	4	2
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		1	1	2
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		7	3	31
Calcium	ppm	ASTM D5185m				
Phoenhorus		AO IIVI DO IOOIII		1770	1781	1901
Phosphorus	ppm	ASTM D5185m		1770 239	254	1901 316
	ppm ppm					
		ASTM D5185m		239	254	316
Zinc	ppm ppm	ASTM D5185m ASTM D5185m	limit/base	239 274	254 301	316 388
Zinc Sulfur	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	limit/base >180	239 274 2968	254 301 2647	316 388 3767
Zinc Sulfur CONTAMINANTS	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method		239 274 2968 current	254 301 2647 history1	316 388 3767 history2
Zinc Sulfur CONTAMINANTS Silicon	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	>180	239 274 2968 current	254 301 2647 history1	316 388 3767 history2
Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m	>180 >20	239 274 2968 current 106 2	254 301 2647 history1 38 <1	316 388 3767 history2 ▲ 194 <1
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	>180 >20 >20	239 274 2968 current 106 2	254 301 2647 history1 38 <1	316 388 3767 history2 194 <1 2
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m method	>180 >20 >20	239 274 2968 current 106 2 0	254 301 2647 history1 38 <1 0	316 388 3767 history2 ▲ 194 <1 2
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D5185m	>180 >20 >20	239 274 2968 current 106 2 0 current	254 301 2647 history1 38 <1 0 history1	316 388 3767 history2 ▲ 194 <1 2 history2 0.1
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm Abs/cm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D5185m *ASTM D7624	>180 >20 >20	239 274 2968 current 106 2 0 current 0 5.8	254 301 2647 history1 38 <1 0 history1 0 5.2	316 388 3767 history2 ▲ 194 <1 2 history2 0.1 6.1
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm Abs/cm	ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D5185m *ASTM D7844 *ASTM D7624 *ASTM D7415	>180 >20 >20 >20 limit/base	239 274 2968 current 106 2 0 current 0 5.8 22.0	254 301 2647 history1 38 <1 0 history1 0 5.2 16.9	316 388 3767 history2 ▲ 194 <1 2 history2 0.1 6.1 26.0
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm ppm ppm ppm Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m  method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m  *ASTM D5185m  *ASTM D7844  *ASTM D7624  *ASTM D7415  method  *ASTM D7414	>180 >20 >20 >20 limit/base	239 274 2968	254 301 2647 history1 38 <1 0 history1 0 5.2 16.9 history1	316 388 3767 history2 ▲ 194 <1 2 history2 0.1 6.1 26.0 history2




# **OIL ANALYSIS REPORT**












VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual		NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPER	HES	metnoa	ilmit/base	current	nistory i	nistory2
Visc @ 100°C	cSt	ASTM D445	13.4	13.4	13.1	13.7


20 Severe			1			
Abnorma	Lucial		M	1		
10	1	1.	11	M		
5-1	1	V		1	./	~^
Apr19/23	ulb/23	1/23	1/23	2/23	1724	1/24
pr1	and it is	Sep2	0ct30/	)ec12/	Jan 22/	Mar7/2
























Laboratory Sample No.

: WC0877015 Lab Number : 06148894 Unique Number : 10978972

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 15 Apr 2024 **Tested** 

: 16 Apr 2024 Diagnosed : 17 Apr 2024 - Sean Felton **EDL NA Recips-Byron Center** 

Byron Center Powerstation, 10310 South Kent Road Byron Center, MI US 49315

Test Package : MOB 2 Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T:

F:

Contact: Jake Ripke

Jake.Ripke@edlenergy.com