


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER AS 30 1431885 (S/N 325778)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Mar2017 Sep2	017 Apr2018 Oct2018 Apr21	019 Nov2019 May2020 Apr2021 May2	123 Aprž024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA015318	KCPA001964	KCP35642
Sample Date		Client Info		09 Apr 2024	23 May 2023	15 Apr 2021
Machine Age	hrs	Client Info		14247	12478	8329
Oil Age	hrs	Client Info		1769	0	0
Oil Changed		Client Info		Not Changd	N/A	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	0	0	0
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm	ASTM D5185m	>50	3	3	2
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	<1
Barium	ppm	ASTM D5185m	90	25	<1	25
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	100	65	34	83
Calcium	ppm	ASTM D5185m	0	<1	0	1
Phosphorus	ppm	ASTM D5185m	0	0	2	2
Zinc	ppm	ASTM D5185m	0	<1	1	0
Sulfur	ppm	ASTM D5185m	23500	18059	24197	18602
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	2
Sodium	ppm	ASTM D5185m		18	5	17
Potassium	ppm	ASTM D5185m	>20	0	<1	2
Water	%	ASTM D6304		0.014	0.011	0.015
ppm Water	ppm	ASTM D6304	>500	142	111.1	152.6
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		12707	30069	9772
Particles >6µm		ASTM D7647	>1300	4035	<u>▲</u> 11383	<u>\$\times\$ 2586</u>
Particles >14μm		ASTM D7647	>80	<u>^</u> 235	4 994	<u>^</u> 202
Particles >21µm		ASTM D7647	>20	49	<u></u> 196	<u>4</u> 7
Dortiolog - 20um		ASTM D7647	>4	1	<u>13</u>	1
Particles >38µm						
Particles >36µm Particles >71µm		ASTM D7647	>3	0	0	0
		ASTM D7647 ISO 4406 (c)	>3 >/17/13	0 <u>^</u> 21/19/15	0 <u>22/21/17</u>	0 ▲ 19/15



OIL ANALYSIS REPORT







Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

: KCPA015318 Lab Number : 06149519 Unique Number: 10979597

Received **Tested**

Diagnosed : 17 Apr 2024 - Don Baldridge Test Package : IND 2 (Additional Tests: KF, PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

: 15 Apr 2024

: 16 Apr 2024

RAUCH 845 PARK PL

US 47150

T:

F:

NEW ALBANY, IN

Contact: SERVICE MANAGER