

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id 9043629 (S/N NOT GIVEN)

Compressor Fluid KAESER SIGMA (OEM) S-460 (--- QTS)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number		Client Info		KC130671	KCPA009123	
Sample Date		Client Info		11 Apr 2024	30 Oct 2023	
Machine Age	hrs	Client Info		5250	1317	
Oil Age	hrs	Client Info		2500	0	
Oil Changed		Client Info		Changed	N/A	
Sample Status				ABNORMAL	ABNORMAL	
-		and the set	1			
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	3	10	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>50	<1	1	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	0	0	
Molybdenum	ppm	ASTM D5185m		0	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	90	0	0	
Calcium	ppm	ASTM D5185m	2	0	1	
Phosphorus	ppm	ASTM D5185m		32	51	
Zinc	ppm	ASTM D5185m		0	0	
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	
Sodium	ppm	ASTM D5185m	220	2	<1	
Potassium	ppm	ASTM D5185m	>20	0	0	
Water	%	ASTM D6304		0.003	0.004	
ppm Water	ppm	ASTM D6304	>500	36	46.9	
FLUID CLEANLIN		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647			17138	
Particles >6µm		ASTM D7647	>1300		▲ 3630	
Particles >14µm		ASTM D7647	>80		▲ 162	
Particles >21µm		ASTM D7647 ASTM D7647			▲ 29	
Particles >38µm		ASTM D7647 ASTM D7647	>20		0	
Particles >71µm		ASTM D7647 ASTM D7647	>3		0	
Oil Cleanliness		ISO 4406 (c)	>/17/13		0 ▲ 21/19/15	
		()				
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.23	0.18	



42 Abnormal 40 38

OIL ANALYSIS REPORT

0000 Severe	
8000	
6000 -	
4000	
2000	
0 Abnormal	
0 ct3 0/23	Apr11/24
0	A
Water (KF)	
2000 - Severe	
8000	
6000-	
4000	
2000 -	
Abnormal	
0 ct30/23	Apr11/24
0	Ap
Viscosity @ 40°C	
52 Abnormal	
50	1

	VISUAL		method	limit/bas	e current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
	Precipitate	scalar	*Visual	NONE	NONE	NONE	
	Silt	scalar	*Visual	NONE	NONE	NONE	
	Debris	scalar	*Visual	NONE	🔺 MODER	NONE	
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Apr11/24	Appearance	scalar	*Visual	NORML	NORML	NORML	
Ap	Odor	scalar	*Visual	NORML	NORML	NORML	
	Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
	Free Water	scalar	*Visual		NEG	NEG	
	FLUID PROPERT	IES	method	limit/bas	e current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	47.4	48.1	
	SAMPLE IMAGES	S	method	limit/bas	e current	history1	history2
Apr11/24	Color						no image
	Bottom						no image
A1	Non-ferrous Metal	s		Apri 1/24			
	Viscosity @ 40°C			Apri1/24	Acid Number		
	55 T			(D	Acid Number		
	50 - Abnormal			KOH/	0.40 - Base		
	Base Abnormal			Acid Number (mg KOH/g)	0.30 -		
	성 <mark>Abnormal</mark>			Vumbe	0.20		
	35			Acid N	0.10		
				1/24 -	0.00.1 1/2 1/2		
	0ct30/23			Apr11/24	0ct30/23		
Laboratory	: WearCheck USA - 50			, NC 2751 5 Apr 2024	3	I 111 BUSIN	INDIUM COR

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: INDUTI [WUSCAR] 06149524 (Generated: 04/17/2024 23:44:25) Rev: 1

Contact/Location: Service Manager - INDUTI Page 2 of 2

F: