

OIL ANALYSIS REPORT

Sample Rating Trend





VOLVO A45G 353636 Component Rear Axle

Fluid VOLVO SUPER GEAR OIL 75W-80-GO102 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2			
Sample Number		Client Info		ML0000624					
Sample Date		Client Info		10 Apr 2024					
Machine Age	hrs	Client Info		884					
Oil Age	hrs	Client Info		884					
Oil Changed		Client Info		Changed					
Sample Status				NORMAL					
CONTAMINATION	١	method	limit/base	current	history1	history2			
Water		WC Method	>0.2	NEG					
WEAR METALS		method	limit/base	current	history1	history2			
Iron	ppm	ASTM D5185m	>900	108					
Chromium	ppm	ASTM D5185m	>20	<1					
Nickel	ppm	ASTM D5185m	>10	<1					
Titanium	ppm	ASTM D5185m	-	<1					
Silver	ppm	ASTM D5185m		0					
Aluminum	ppm	ASTM D5185m	>30	<1					
Lead	ppm	ASTM D5185m	>50	0					
Copper	ppm	ASTM D5185m	>150	1					
Tin		ASTM D5185m	>130	0					
Vanadium	ppm	ASTM D5185m	>20	ں <1					
	ppm								
Cadmium	ppm	ASTM D5185m		0					
ADDITIVES		method	limit/base	current	history1	history2			
Boron	ppm	ASTM D5185m		299					
Barium	ppm	ASTM D5185m		3					
Molybdenum	ppm	ASTM D5185m		3					
Manganese	ppm	ASTM D5185m		4					
Magnesium	ppm	ASTM D5185m		6					
Calcium	ppm	ASTM D5185m		84					
Phosphorus	ppm	ASTM D5185m		2359					
Zinc	ppm	ASTM D5185m		37					
Sulfur	ppm	ASTM D5185m		50776					
CONTAMINANTS		method	limit/base	current	history1	history2			
Silicon	ppm	ASTM D5185m	>50	1					
Sodium	ppm	ASTM D5185m		4					
Potassium	ppm	ASTM D5185m	>20	6					
VISUAL		method	limit/base	current	history1	history2			
White Metal	scalar	*Visual	NONE	NONE					
Yellow Metal	scalar	*Visual	NONE	NONE					
Precipitate	scalar	*Visual	NONE	NONE					
Silt	scalar	*Visual	NONE	LIGHT					
Debris	scalar	*Visual	NONE	NONE					
Sand/Dirt	scalar	*Visual	NONE	NONE					
Appearance	scalar	*Visual	NORML	NORML					
Odor	scalar	*Visual	NORML	NORML					
Emulsified Water	scalar	*Visual	>0.2	NEG					
Free Water	scalar	*Visual	-	NEG					
6:07:23) Rev: 1					nitted By: Service - Alex Anderson				



OIL ANALYSIS REPORT



FLUID PROPERTIE	S method	limit/base	current	history1	history2
Visc @ 40°C	St ASTM D44	5	52.8		
SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image
GRAPHS				ļ	
Ferrous Alloys		Apr10/24 Apr			
: WearCheck USA - 501 I : ML0000624 : 06150743 : 10980821	Received : Tested :	ury, NC 27513 16 Apr 2024 17 Apr 2024 18 Apr 2024 - Dor			NT CO - RICHMO UNTAIN RO EN ALLEN, US 230
: CONST	-		-	Contact:	Alex Ander

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (804)266-1611

Certificate L2367

Submitted By: Service - Alex Anderson Page 2 of 2

aanderson@mcclung-logan.com

Т: