

# **OIL ANALYSIS REPORT**

Sample Rating Trend





[W02008185] Wachine Id VOLVO A30F 82248 Component Drop Box

{not provided} (11 GAL)

### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. ( Customer Sample Comment: W02008185 )

Area

## Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


## Fluid Condition

The condition of the oil is acceptable for the time in service.


| SAMPLE INFORM   | IATION           | method             | limit/base    | current       | history1 | history2 |
|---|------------------|--------------------|---------------|---------------|----------|----------|
| Sample Number   |                  | Client Info        |               | ML0001604     |          |          |
| Sample Date   |                  | Client Info        |               | 12 Apr 2024   |          |          |
| Machine Age   | hrs              | Client Info        |               | 14578         |          |          |
| Oil Age   | hrs              | Client Info        |               | 2000          |          |          |
| Oil Changed   |                  | Client Info        |               | Changed       |          |          |
| Sample Status   |                  |                    |               | NORMAL        |          |          |
| CONTAMINATION   | J                | method             | limit/base    | current       | history1 | history2 |
| Water   |                  | WC Method          | >0.2          | NEG           |          |          |
| WEAR METALS   |                  | method             | limit/base    | current       | history1 | history2 |
| Iron  | ppm              | ASTM D5185m        | >500          | 86            |          |          |
| Chromium  | ppm              | ASTM D5185m        | >20           | <1            |          |          |
| Nickel  | ppm              | ASTM D5185m        | >10           | <1            |          |          |
| Titanium  | ppm              | ASTM D5185m        |               | <1            |          |          |
| Silver  | ppm              | ASTM D5185m        |               | <1            |          |          |
| Aluminum  | ppm              | ASTM D5185m        | >30           | 5             |          |          |
| Lead  | ppm              | ASTM D5185m        | >30           | 1             |          |          |
| Copper  | ppm              | ASTM D5185m        | >30           | 1             |          |          |
| Tin   | ppm              | ASTM D5185m        | >20           | 0             |          |          |
| Vanadium  | ppm              | ASTM D5185m        |               | <1            |          |          |
| Cadmium   | ppm              | ASTM D5185m        |               | 0             |          |          |
| ADDITIVES   |                  | method             | limit/base    | current       | history1 | history2 |
| Boron   | ppm              | ASTM D5185m        |               | 202           |          |          |
| Barium  | ppm              | ASTM D5185m        |               | 3             |          |          |
| Molybdenum  | ppm              | ASTM D5185m        |               | 9             |          |          |
| Manganese   | ppm              | ASTM D5185m        |               | 1             |          |          |
| Magnesium   | ppm              | ASTM D5185m        |               | 25            |          |          |
| Calcium   | ppm              | ASTM D5185m        |               | 114           |          |          |
| Phosphorus  | ppm              | ASTM D5185m        |               | 888           |          |          |
| Zinc  | ppm              | ASTM D5185m        |               | 102           |          |          |
| Sulfur  | ppm              | ASTM D5185m        |               | 51531         |          |          |
| CONTAMINANTS  |                  | method             | limit/base    | current       | history1 | history2 |
| Silicon   | ppm              | ASTM D5185m        | >50           | 12            |          |          |
| Sodium  | ppm              | ASTM D5185m        |               | 4             |          |          |
| Potassium   | ppm              | ASTM D5185m        | >20           | 2             |          |          |
| VISUAL  |                  | method             | limit/base    | current       | history1 | history2 |
| White Metal   | scalar           | *Visual            | NONE          | NONE          |          |          |
| Yellow Metal  | scalar           | *Visual            | NONE          | NONE          |          |          |
| Precipitate   | scalar           | *Visual            | NONE          | NONE          |          |          |
|   | scalar           | *Visual            | NONE          | NONE          |          |          |
| SIIL  |                  | *Visual            | NONE          | LIGHT         |          |          |
|   | scalar           | visuai             |               | LIGHT         |          |          |
| Debris  | scalar<br>scalar | *Visual            | NONE          | NONE          |          |          |
| Debris<br>Sand/Dirt   |                  |                    |               |               |          |          |
| Debris<br>Sand/Dirt<br>Appearance                                     | scalar           | *Visual            | NONE          | NONE          |          |          |
| Silt<br>Debris<br>Sand/Dirt<br>Appearance<br>Odor<br>Emulsified Water | scalar<br>scalar | *Visual<br>*Visual | NONE<br>NORML | NONE<br>NORML |          |          |



## **OIL ANALYSIS REPORT**



|  | FLUID PROPERTIES  |  | nethod              | limit/base   | current  | history1 | history2  |
|--|---|--|---------------------|--|----------|----------|---|
| 1  | Visc @ 40°C   | cSt AS                                     | STM D445            |  | 262      |          |   |
|  | SAMPLE IMAGES   | <b>;</b> r                                 | nethod              | limit/base   | current  | history1 | history2  |
| 4  | Color   |  |                     |  | no image | no image | no image  |
| Apr12/24                                       | Bottom  |  |                     |  | no image | no image | no image  |
|  | GRAPHS  |  |                     |  |          |          |   |
|  | Ferrous Alloys  |  |                     |  |          |          |   |
|  | Non-ferrous Metal   | 5  |                     | Apr1224 E  |          |          |   |
|  | Viscosity @ 40°C  | ******                                     |                     | Apr12/24   |          |          |   |
|  | 280<br>260<br>240<br>220  |  |                     |  |          |          |   |
|  | 200<br>180<br>3 160<br>140<br>120<br>Abarmal                    |  |                     |  |          |          |   |
|  | Abnormal<br>Abnormal<br>80<br>+7272100<br>W                     |  |                     | Apr12/24   |          |          |   |
| ooratory<br>mple No.<br>o Number<br>que Number | : WearCheck USA - 50<br>: ML0001604<br>: 06150759<br>: 10980837 | Madison A<br>Received<br>Tested<br>Diagnos | <b>d</b> :16<br>:17 | NC 27513<br>Apr 2024<br>Apr 2024<br>Apr 2024 - Dor |          |          | IT CO - MANASS/<br>UARRY ROA<br>ANASSAS, V<br>US 2011 |



Report Id: VOLVO0002 [WUSCAR] 06150759 (Generated: 04/23/2024 12:07:10) Rev: 1

Submitted By: DARRELL ANDES

Contact: MIKE MAYHUGH

Page 2 of 2

T: (703)393-7344

F: (703)393-7844