

OIL ANALYSIS REPORT

Sample Rating Trend





[W02008186] Wachine for VOLVO A30D 14025 Component

Component Bogie/Center Axle Fluid {not provided} (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: W02008186)

Area

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

hrs hrs	Client Info Client Info Client Info		ML0001594 12 Apr 2024		
			12 Apr 2024		
	Client Info				
hrs			21012		
	Client Info		2000		
	Client Info		Changed		
			NORMAL		
J	method	limit/base	current	history1	history2
	WC Method	>0.2	NEG		
	method	limit/base	current	history1	history2
ppm	ASTM D5185m	>900	265		
ppm	ASTM D5185m	>20	3		
ppm	ASTM D5185m	>10	2		
ppm	ASTM D5185m		1		
ppm	ASTM D5185m		0		
ppm	ASTM D5185m	>30	2		
ppm	ASTM D5185m	>50	<1		
ppm	ASTM D5185m	>150	10		
		>20	0		
	ASTM D5185m		<1		
ppm	ASTM D5185m		0		
	method	limit/base	current	history1	history2
ppm	ASTM D5185m		174		
	ASTM D5185m		2		
ppm	ASTM D5185m		1		
	ASTM D5185m		5		
	ASTM D5185m		12		
	ASTM D5185m		246		
	ASTM D5185m		905		
	ASTM D5185m				
ppm	ASTM D5185m		46088		
	method	limit/base	current	history1	history2
ppm	ASTM D5185m	>50	8		
ppm	ASTM D5185m		2		
ppm	ASTM D5185m	>20	3		
	method	limit/base	current	history1	history2
scalar	*Visual	NONE	NONE		
scalar	*Visual	NONE	NONE		
scalar	*Visual	NONE	NONE		
scalar	*Visual	NONE	NONE		
scalar	*Visual	NONE	NONE		
scalar	*Visual	NONE	NONE		
scalar	*Visual	NORML	NORML		
scalar	*Visual	NORML	NORML		
scalar	*Visual	>0.2	NEG		
	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	WC MethodPpmASTM D5185mPpmASTM D5185m <t< td=""><th>WC Method>0.2ppmASTM D5185m>900ppmASTM D5185m>20ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>30ppmASTM D5185m>30ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>20ppmASTM D5185m>20ppmASTM D5185m>20ppmASTM D5185mppmASTM D5185m</th><td>WC Method>0.2NEGppmASTM D5185m>900265ppmASTM D5185m>203ppmASTM D5185m>102ppmASTM D5185m>102ppmASTM D5185m>302ppmASTM D5185m>50<1</td>ppmASTM D5185m>15010ppmASTM D5185m>15010ppmASTM D5185m>200ppmASTM D5185m>200ppmASTM D5185m>200ppmASTM D5185m>200ppmASTM D5185m>200ppmASTM D5185m0ppmASTM D5185m20ppmASTM D5185m174ppmASTM D5185m12ppmASTM D5185m12ppmASTM D5185m246ppmASTM D5185m246ppmASTM D5185m22ppmASTM D5185m22ppmASTM D5185m22ppmASTM D5185m22ppmASTM D5185m20ppmASTM D5185m22ppmASTM D5185m20ppmASTM D5185m20ppmASTM D5185m20ppmASTM D5185m20ppmASTM D5185m20ppmASTM D5185m20ppmASTM D5185m20ppmASTM D5185m20ppmASTM D5185m20</t<>	WC Method>0.2ppmASTM D5185m>900ppmASTM D5185m>20ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>30ppmASTM D5185m>30ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>10ppmASTM D5185m>20ppmASTM D5185m>20ppmASTM D5185m>20ppmASTM D5185mppmASTM D5185m	WC Method>0.2NEGppmASTM D5185m>900265ppmASTM D5185m>203ppmASTM D5185m>102ppmASTM D5185m>102ppmASTM D5185m>302ppmASTM D5185m>50<1	WC Method >0.2 NEG method limit/base current history1 ppm ASTM D5185m >900 2655 ppm ASTM D5185m >20 3 ppm ASTM D5185m >10 2 ppm ASTM D5185m >10 2 ppm ASTM D5185m >30 2 ppm ASTM D5185m >50 <1



OIL ANALYSIS REPORT



	PERTIES	method	limit/base	current	history1	history
Visc @ 40°C	cSt	ASTM D445		273		
SAMPLE IM	AGES	method	limit/base	current	history1	history
Color				no image	no image	no image
Bottom				no image	no image	no image
GRAPHS						
Ferrous Alloy	/S					
250 - iron iron chromium nickel	n					
200 -						
톱 150 -						
100						
50 -						
Apr12/24 -			Apr12/24 -			
₹ Non-ferrous	Motals		Ap			
¹⁰ I	Metals					
8 - tin						
7						
E 5-						
4						
2						
Apr12/24			Apr12/24			
Viscosity @ 4	40°C		-			
260						
240 - 220						
200						
() 180 - 승산 경 160 -						
Abnormal						
100 Abnormal						
1			Apr12/24			

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (703)378-8300 F:

Certificate L2367

Submitted By: DARRELL ANDES Page 2 of 2