

# **OIL ANALYSIS REPORT**

Sample Rating Trend



NORMAL



[W02008184] Wachine Id VOLVO L70H 622516 Component Front Axle

Fluid VOLVO SUPER WET BRAKE TRANSAXLE OIL WB102 (9 GAL)

SAMPLE INFORMATION method

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. ( Customer Sample Comment: W02008184 )

Area

# Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


## **Fluid Condition**

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		ML0001085		
Sample Date		Client Info		12 Apr 2024		
Machine Age	hrs	Client Info		10145		
Oil Age	hrs	Client Info		2000		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
		and the set	Paral II.		la facta a su af	le le terrer de
CONTAMINATION		method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	9		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>10	<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		<1		
Aluminum	ppm	ASTM D5185m	>30	4		
Lead	ppm	ASTM D5185m	>50	0		
Copper	ppm	ASTM D5185m	>120	<1		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		137		
Barium	ppm	ASTM D5185m		4		
Molybdenum	ppm	ASTM D5185m		5		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		28		
Calcium	ppm	ASTM D5185m		4123		
Phosphorus	ppm	ASTM D5185m		1261		
Zinc	ppm	ASTM D5185m		1502		
Sulfur	ppm	ASTM D5185m		7989		
			11 1.0			
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	13		
Sodium	ppm	ASTM D5185m		6		
Potassium	ppm	ASTM D5185m	>20	0		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
	Scalai	1.00.00				
Silt	scalar	*Visual	NONE	NONE		
			NONE NONE	NONE NONE		
Debris	scalar	*Visual				
Debris Sand/Dirt	scalar scalar	*Visual *Visual	NONE	NONE		
Debris Sand/Dirt Appearance	scalar scalar scalar	*Visual *Visual *Visual	NONE NONE	NONE NONE		
Silt Debris Sand/Dirt Appearance Odor Emulsified Water	scalar scalar scalar scalar	*Visual *Visual *Visual *Visual	NONE NORML	NONE NONE NORML		



# **OIL ANALYSIS REPORT**



FLUID PROF	PERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	55	46.8		
SAMPLE IMA	AGES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image
GRAPHS					:	
Ferrous Alloys	S					
9 - iron 8 - nickel						
7-						
E 5-						
4						
2						
			-			
Apr12/24			Apr12/24			
Non-ferrous N	Metals					
9 copper						
8 tin						
6- E_ 5-						
4-						
3						
1						
apr12/24			Apr12/24			
∛ Viscosity @ 4	0°C		Ap			
70 T						
65						
60 - Base						
(2, 55 - Base 						
45 -						
40 -						
35						
Apr12/24			Apr12/24			
4			4			
: WearCheck USA : ML0001085	- 501 Madisor <b>Recei</b> v		, NC 27513 Apr 2024		W	LLIAM HAZE PO BOX 60
r : 06150767	Testeo	<b>d</b> :17	Apr 2024	Baldridaa	С	HANTILLY, V
r :10980845 e :CONST	Diagn	<b>used</b> :18	Apr 2024 - Dor	i Baidridge	Contact: SERVI	US 2015 CE MANAGE

Contact: SERVICE MANAGER Test Package : CONST Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (703)378-8300 F: