

# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# KAESER SX 6 2722484 (S/N 2082)

Component Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

## **DIAGNOSIS**

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is a high amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Feb 2020	Nov2020	Oct2021 Nov2022	Mar2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KC06151159	KC05694104	KC05391952
Sample Date		Client Info		20 Mar 2024	03 Nov 2022	26 Oct 2021
Machine Age	hrs	Client Info		10373	5547	4698
Oil Age	hrs	Client Info		0	0	4698
Oil Changed		Client Info		N/A	N/A	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	<1	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m		<1	0	<1
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m		11	19	25
Tin	ppm	ASTM D5185m	>10	<1	0	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	18
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		1	0	0
Magnesium	ppm	ASTM D5185m	90	12	0	2
Calcium	ppm	ASTM D5185m	2	<1	0	0
Phosphorus	ppm	ASTM D5185m		0	1	0
Zinc	ppm	ASTM D5185m		0	0	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	<1
Sodium	ppm	ASTM D5185m		4	<1	1
Potassium	ppm	ASTM D5185m	>20	2	0	0
Water	%	ASTM D6304	>0.05	0.007	0.012	0.007
ppm Water	ppm	ASTM D6304	>500	75	127.0	70.5
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		20791	31569	23100
Particles >6μm		ASTM D7647	>1300	<u>A</u> 8416	<b>△</b> 9920	<u>▲</u> 6603
Particles >14μm		ASTM D7647	>80	<u> </u>	<u>▲</u> 1892	<b>▲</b> 938
Particles >21µm		ASTM D7647	>20	<b>452</b>	<b>▲</b> 859	<b>▲</b> 371
Particles >38μm		ASTM D7647	>4	<u>^</u> 28	<u>^</u> 70	<b>△</b> 23
Particles >71μm		ASTM D7647		1	3	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>22/20/18</u>	<u>22/20/18</u>	△ 20/17
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.41	0.39	0.359



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

Lab Number : 06151159 Unique Number : 10981237

: KC06151159

Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 16 Apr 2024 **Tested** : 19 Apr 2024

Diagnosed : 19 Apr 2024 - Don Baldridge

**OLD DOMINION** 347 HENRY D ROBINSON BLVD

PENDERGRASS, GA US 30567

Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: OLDPENKC [WUSCAR] 06151159 (Generated: 04/19/2024 15:10:48) Rev: 1

Contact/Location: Service Manager - OLDPENKC

T:

F: