


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# **7285136 (S/N 1226)**Component Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

### **DIAGNOSIS**

#### Recommendation

The oil change at the time of sampling has been noted. We recommend you service the filters on this component. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is a high amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Feb 2023	Apr2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA016813	KCP46356	
Sample Number		Client Info		02 Apr 2024	20 Feb 2023	
Machine Age	hrs	Client Info		6265	3469	
Oil Age	hrs	Client Info		0	3469	
Oil Changed	1110	Client Info		Changed	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm		>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	<1	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	<1	<1	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m		15	24	
Tin	ppm	ASTM D5185m	>10	<1	0	
Vanadium	ppm	ASTM D5185m	>10	0	0	
Cadmium	ppm	ASTM D5185m		0	0	
	ррпп		Uses It flags as a second			
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	
Barium	ppm	ASTM D5185m	90	0	2	
Molybdenum	ppm	ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m		1	0	
Magnesium	ppm	ASTM D5185m	100	7	11	
Calcium	ppm	ASTM D5185m	0	<1	0	
Phosphorus	ppm	ASTM D5185m	0	2	10	
Zinc	ppm	ASTM D5185m	0	0	12	
Sulfur	ppm	ASTM D5185m	23500	24071	15966	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2	<1	
Sodium	ppm	ASTM D5185m		3	<1	
Potassium	ppm	ASTM D5185m	>20	3	3	
Water	%	ASTM D6304	>0.05	0.005	0.006	
ppm Water	ppm	ASTM D6304	>500	58	60.7	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		14190	56704	
Particles >6μm		ASTM D7647	>1300	<u>▲</u> 6790	<u>^</u> 23480	
Particles >14μm		ASTM D7647	>80	<u>^</u> 764	<u>479</u>	
Particles >21µm		ASTM D7647	>20	<u> </u>	<u>44</u>	
Particles >38μm		ASTM D7647	>4	<u>^</u> 6	1	
Particles >71μm		ASTM D7647	>3	1	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>^</u> 21/20/17	<u>\$\text{23/22/16}\$</u>	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.45	0.34	



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06151222

: KCPA016813 Unique Number : 10981300

Received : 16 Apr 2024 **Tested** Diagnosed

: 19 Apr 2024 : 19 Apr 2024 - Don Baldridge

Test Package : IND 2 ( Additional Tests: KF, PrtCount )

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

126 CHESTNUT ST WARWICK, RI US 02888

Contact: Service Manager

T: F: