

## **OIL ANALYSIS REPORT**

Sample Rating Trend



### Area **KAESER 1141 - MIDWEST TUNADUM SERVICE** Component Compressor

#### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UDI0000121		
Sample Date		Client Info		09 Apr 2024		
Machine Age	hrs	Client Info		37836		
Oil Age	hrs	Client Info		2800		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>3	0		
Titanium	ppm	ASTM D5185m	>3	0		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	0		
Lead	ppm	ASTM D5185m	>10	0		
Copper	ppm	ASTM D5185m	>50	2		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		28		
Calcium	ppm	ASTM D5185m		2		
Phosphorus	ppm	ASTM D5185m		0		
Zinc	ppm	ASTM D5185m		9		
Sulfur	ppm	ASTM D5185m		20764		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0		
Sodium	ppm	ASTM D5185m		5		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.35		



# **OIL ANALYSIS REPORT**

VISUAL





White Metal Yellow Metal						
Yellow Metal	scalar	*Visual	NONE	NONE		
	scalar	*Visual	NONE	NONE		
Precipitate		*Visual	NONE	NONE		
Silt		*Visual	NONE	NONE		
Debris		*Visual	NONE	NONE		
Sand/Dirt		*Visual	NONE	NONE		
Appearance		*Visual	NORML	NORML		
Odor		*Visual	NORML	NORML		
Emulsified Water		*Visual	>0.05	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPER	TIES	method	limit/base	current	history1	history
Visc @ 40°C	cSt	ASTM D445		44.6		
SAMPLE IMAGE	ES	method	limit/base	current	history1	history
Color					no image	no image
Bottom					no image	no image
Non-ferrous Meta	als		Apr3/24			
0			<u><u>n</u></u>			
Viscosity @ 40°C	2		Acid Number (mg K0H/g) 01:0 (mg K0H/g)	Acid Number		

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCDELDOW [WUSCAR] 06152073 (Generated: 04/20/2024 09:55:37) Rev: 1

Certificate L2367

F: (630)960-3931 Contact/Location: MICHAEL FERRIS - UCDELDOW

Page 2 of 2

T: