




# OIL ANALYSIS REPORT



Machine Id  
**CATERPILLAR D6 LGP 10041 (S/N KEW01161)**  
 Component  
**Right Final Drive**  
 Fluid  
**{not provided} (--- GAL)**

### Sample Rating Trend



**NORMAL**



### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.  
 Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0913255</b>	WC0888057	WC0887958
Sample Date	Client Info			<b>09 Apr 2024</b>	04 Feb 2024	03 Jan 2024
Machine Age	hrs	Client Info		<b>3152</b>	2664	2112
Oil Age	hrs	Client Info		<b>488</b>	540	453
Oil Changed	Client Info			<b>Changed</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Water	WC Method		>0.2	<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>800	<b>12</b>	8	8
Chromium	ppm	ASTM D5185m	>10	<b>1</b>	<1	0
Nickel	ppm	ASTM D5185m	>5	<b>1</b>	0	0
Titanium	ppm	ASTM D5185m	>15	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m	>2	<b>&lt;1</b>	0	0
Aluminum	ppm	ASTM D5185m	>75	<b>1</b>	0	0
Lead	ppm	ASTM D5185m	>10	<b>1</b>	0	0
Copper	ppm	ASTM D5185m	>75	<b>&lt;1</b>	0	0
Tin	ppm	ASTM D5185m	>8	<b>1</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>1</b>	0	0


ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<b>166</b>	138	154
Barium	ppm	ASTM D5185m		<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185m		<b>8</b>	13	0
Manganese	ppm	ASTM D5185m		<b>1</b>	<1	0
Magnesium	ppm	ASTM D5185m		<b>35</b>	75	0
Calcium	ppm	ASTM D5185m		<b>756</b>	1519	44
Phosphorus	ppm	ASTM D5185m		<b>598</b>	824	313
Zinc	ppm	ASTM D5185m		<b>261</b>	539	3
Sulfur	ppm	ASTM D5185m		<b>2870</b>	2940	1788

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>400	<b>7</b>	4	2
Sodium	ppm	ASTM D5185m		<b>&lt;1</b>	3	0
Potassium	ppm	ASTM D5185m	>20	<b>5</b>	6	0

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG	NEG
Free Water	scalar	*Visual		<b>NEG</b>	NEG	NEG



# OIL ANALYSIS REPORT






FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	91.6	85.6	95.4

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color				no image	no image	no image
Bottom				no image	no image	no image

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0913255      **Received** : 17 Apr 2024  
**Lab Number** : 06152390      **Tested** : 18 Apr 2024  
**Unique Number** : 10982468      **Diagnosed** : 18 Apr 2024 - Wes Davis  
**Test Package** : CONST

**TRADER CONSTRUCTION CO.**  
 PO DRAWER 1578  
 NEW BERN, NC  
 US 28563  
 Contact: MIKE WYATT  
 mwyatt@traderconstruction.com  
 T: (252)633-1399  
 F: (252)638-4871

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)