




# OIL ANALYSIS REPORT

Area  
**PIONEER RESOUCE**  
 Machine Id  
**JCB 457 3224056**  
 Component  
**Diesel Engine**  
 Fluid  
**JCB 15W40 (28 QTS)**

### Sample Rating Trend



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

Metal levels are typical for a components first oil change.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>JCB005194</b>	---	---
Sample Date	Client Info		<b>01 Apr 2024</b>	---	---
Machine Age	hrs	Client Info	<b>859</b>	---	---
Oil Age	hrs	Client Info	<b>859</b>	---	---
Oil Changed	Client Info		<b>N/A</b>	---	---
Sample Status			<b>NORMAL</b>	---	---

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	---	---
Water	WC Method	>0.2	<b>NEG</b>	---	---
Glycol	WC Method		<b>NEG</b>	---	---

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >125	<b>56</b>	---	---
Chromium	ppm	ASTM D5185m >5	<b>5</b>	---	---
Nickel	ppm	ASTM D5185m >4	<b>2</b>	---	---
Titanium	ppm	ASTM D5185m	<b>2</b>	---	---
Silver	ppm	ASTM D5185m >3	<b>0</b>	---	---
Aluminum	ppm	ASTM D5185m >25	<b>4</b>	---	---
Lead	ppm	ASTM D5185m >15	<b>1</b>	---	---
Copper	ppm	ASTM D5185m >125	<b>75</b>	---	---
Tin	ppm	ASTM D5185m >4	<b>2</b>	---	---
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	---	---
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	---	---

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	<b>0</b>	---	---
Barium	ppm	ASTM D5185m	<b>6</b>	---	---
Molybdenum	ppm	ASTM D5185m	<b>3</b>	---	---
Manganese	ppm	ASTM D5185m	<b>6</b>	---	---
Magnesium	ppm	ASTM D5185m	<b>52</b>	---	---
Calcium	ppm	ASTM D5185m	<b>2303</b>	---	---
Phosphorus	ppm	ASTM D5185m	<b>937</b>	---	---
Zinc	ppm	ASTM D5185m	<b>1066</b>	---	---
Sulfur	ppm	ASTM D5185m	<b>3779</b>	---	---

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >50	<b>35</b>	---	---
Sodium	ppm	ASTM D5185m	<b>5</b>	---	---
Potassium	ppm	ASTM D5185m >20	<b>4</b>	---	---

## INFRA-RED





	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.3</b>	---	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>7.5</b>	---	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.0</b>	---	---

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>11.1</b>	---	---
Base Number (BN)	mg KOH/g	ASTM D2896	<b>6.1</b>	---	---











# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	98.6	---	---
Visc @ 100°C	cSt	ASTM D445	13.2	---	---
Viscosity Index (VI)	Scale	ASTM D2270	132	---	---

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : JCB005194      **Received** : 18 Apr 2024  
**Lab Number** : **06152955**      **Tested** : 19 Apr 2024  
**Unique Number** : 10983033      **Diagnosed** : 19 Apr 2024 - Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: KV40, TBN, VI )

**JCB OF AUSTIN - ENERCO LLC - MANOR**  
 12916 EAST US HWY 290  
 MANOR, TX  
 US 78653  
 Contact:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: