


# **OIL ANALYSIS REPORT**

Sample Rating Trend







# ALSTOM 3520

Hydraulic System

**ESSO UNIVIS N 32 (55 GAL)** 

DI	$^{\prime}$	чι	$\sim$	U	${}^{\circ}$

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.


## **Fluid Condition**


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		Apr2011	Apr2013 Apr2015	Apr2017 Apr2022	Apr2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0909831	WC0643738	WC0592299
Sample Date		Client Info		17 Apr 2024	09 Apr 2023	08 Apr 2022
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ATTENTION	NORMAL
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0	<1	2
Chromium	ppm	ASTM D5185m	>10	<1	1	2
Nickel	ppm	ASTM D5185m	>10	3	11	15
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	<1	<1
Lead	ppm	ASTM D5185m	>10	7	13	7
Copper	ppm	ASTM D5185m	>75	3	5	4
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	.1	0	0	<1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m	.3	0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m	0	<1	0	0
Calcium	ppm	ASTM D5185m	74	48	51	48
Phosphorus	ppm	ASTM D5185m	266	340	354	341
Zinc	ppm	ASTM D5185m	338	425	454	363
Sulfur	ppm	ASTM D5185m		2339	2682	2165
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<1	<1	<1
Sodium	ppm	ASTM D5185m		2	<1	1
Potassium	ppm	ASTM D5185m	>20	1	0	0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	2936	13054	4499
Particles >6µm		ASTM D7647	>1300	408	2439	636
Particles >14μm		ASTM D7647	>160	24	111	63
Particles >21µm		ASTM D7647	>40	6	23	26
Particles >38µm		ASTM D7647	>10	0	2	2
Particles >71μm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/17/14	19/16/12	21/18/14	19/16/13




# **OIL ANALYSIS REPORT**









FLUID DEGRADA	TION	method	limit/base	current	history1	history2	
Acid Number (AN)	mg KOH/g	ASTM D8045		0.38	0.40	0.35	
VISUAL		method				history2	
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	NORML	
<b>Emulsified Water</b>	scalar	*Visual	>0.1	NEG	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	NEG	
FLUID PROPERT	IES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D445	32	32.6	31.0	30.4	
SAMPLE IMAGES	6	method	limit/base	current	history1	history2	
			_				

GRA	PHS										
	ous Alloy	s					icle Cou	nt			
20	iron			1		22,880 <b>Severe</b>					I 26
	chromium nickel	- The state of the		-		1					22
0				***************************************	distance of the last of the la	30,720 Abnom	ıal				
Apr23/11	Apr21/13	Apr20/15	Apr19/17	Apr8/22	Apr17/24 .	7,680					18 16 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
Apr	Apri	Apri	Apr	Ap	April	1,920	1				-18
	ferrous I	Metals			Apr17/24	480-	1				16
20	copper					120	1				14
10+	lead tin	Name of Street, Street, or other Desired in column 2 is not a second or other Desired in column 2 is not a seco	Street or other Designation of the last of		number of	30+		/			12
	un			100	~	8			\		10
0	<u>E</u>	5	-	22	24				1		
Apr23/1	Apr21/13	Apr20/15	Apr19/17	Apr8/22	Apr17/24	-			,	/	To
	sity @ 4					<sup>0</sup> <sub>4μ</sub> Acic	6μ l Numbe	14μ r	21μ	38μ	71 <sup>6</sup>
A 1	nal					E 1.00	TIT	77777			
35 - Abnom	nal					0.50		_			
20	/13	115	-11/	/22+	724	0.00 Acid	/13	/15	-71/	/22	724
Apr23/1	Apr21/13	Apr20/15	Apr19/17	Apr8/22	Apr17/24	Apr23/1	Apr21/13	Apr20/15	Apr19/17	Apr8/22	Apr17/24





Certificate 12367

Laboratory Sample No.

Lab Number : 06153044 Unique Number : 10983122

: WC0909831 Test Package : MOB 2

Color

Bottom

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 18 Apr 2024 **Tested** 

: 19 Apr 2024 : 19 Apr 2024 - Wes Davis Diagnosed

1401 W STREET NE, HIGH SPEED RAIL 2ND FLOOR

WASHINGTON, DC US 20018 Contact: MICHAEL PORTER michael.porter@amtrak.com T: (202)870-1399

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**AMTRAK**