


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



GUAY SON [CONHER] IBACO BM ISMAR II

Transmission (Manual)

RALOY SAE 50 (40 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Fluid: Raloy SAE 50)

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid. The amount and size of particulates present in the system are acceptable.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.


		Mar2022	0ct2022 Apr2023	Sep 2023 Nov2023	Mar2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KL0014207	KL0013401	KL0012852
Sample Date		Client Info		20 Mar 2024	14 Nov 2023	20 Sep 2023
Machine Age	hrs	Client Info		15348	13688	12985
Oil Age	hrs	Client Info		2060	400	10
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	ABNORMAL
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	6	10	5
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>5	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>7	0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	<1	<1
Lead	ppm	ASTM D5185m	>45	<1	<1	0
Copper	ppm	ASTM D5185m	>225	7	6	3
Tin	ppm	ASTM D5185m	>10	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	2	2
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		1	<1	<1
Magnesium	ppm	ASTM D5185m		7	10	15
Calcium	ppm	ASTM D5185m		3439	3387	3528
Phosphorus	ppm	ASTM D5185m		1019	978	991
Zinc	ppm	ASTM D5185m		835	851	876
Sulfur	ppm	ASTM D5185m		7971	6638	6710
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>125	10	12	19
Sodium	ppm	ASTM D5185m		3	<1	<1
Potassium	ppm	ASTM D5185m	>20	0	<1	0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		14162	43395	69242
Particles >6µm		ASTM D7647	>2500	1530	1515	<u></u> 11300
Particles >14μm		ASTM D7647	>320	54	42	187
Particles >21µm		ASTM D7647	>80	13	10	32
Particles >38μm		ASTM D7647	>20	1	1	2
Particles >71µm		ASTM D7647	>4	0	0	1
Particles >71µm Oil Cleanliness		ASTM D7647 ISO 4406 (c)	>4 >18/15	0 18/13	0 18/13	1 ^ 21/15
	TION					


0.72




OIL ANALYSIS REPORT









VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		200	201	205

SAMPLE IMAGES	method			
		1		
Color		-	a	



GRA	APHS									
Ferr	ous Alloys	_		491,		cle Coun	t			т26
15-	iron chromium nickel			122,						-24
5-				30,	720					-22
0 2		13 23	2	7.	680	1				-20 8
Mar28/22	Oct7/22	Apr6/23 - Sep20/23 -	Nov14/23	Mar20/24 s (per 1 ml)	920-	1:	`			-18 :1
Non	-ferrous Me		_	- 45	480 -	1	`			+20 ISO 4408:1999 Cleanliness Code
10 8	copper				120-		1			-14 es
E 6-	tin			E C	30-		1			12 Gode
2		~			8 Serwe mal			1		10
727_0	/22	733	7.23		2			1	\	-8
Mar28/22	0ct7/22	Apr6/23 Sep20/23	Nov14/23	Mar20/24	0					
Visc 250 Abno	osity @ 40°	C		H/g)		^{6µ} Number	14μ	21μ	38μ	71μ
(200 - Abno				er (mg K0	0.8 0.6 0.4 0.2		_			
් 150 - Abno	mal			Mmbe	0.4					
Mar28/22	0ct7/22	Apr6/23 + Sep 20/23 +	Nov14/23 +	Mar20/24 +	Mar28/22	0ct7/22	Apr6/23	Sep20/23	Nov14/23	Mar20/24





Certificate 12367

Laboratory Sample No.

Lab Number : 06153089 Unique Number : 10983167

: KL0014207

Bottom

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received **Tested**

: 18 Apr 2024 : 19 Apr 2024 Diagnosed

: 22 Apr 2024 - Angela Borella

HERMOSILLO, MX 83140 Contact: EDUARDO GARCIA egarcia.comsa@gmail.com T: (526)622-1581 x:81

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Test Package : MOB 2 (Additional Tests: PrtCount)

F: x: Submitted By: EDUARDO GARCIA

CONOR

JUAREZ 348