

OIL ANALYSIS REPORT

Area NOT GIVEN Machine Id QUINCY CAI858062 - VENTRA GR 5 Component

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.






NORMAL


SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06153226		
Sample Date		Client Info		12 Apr 2024		
Machine Age	hrs	Client Info		27790		
Oil Age	hrs	Client Info		2520		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		601		
Zinc	ppm	ASTM D5185m		45		
Sulfur	ppm	ASTM D5185m		1143		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	2		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.26		



OIL ANALYSIS REPORT

VISUAL





	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
	Appearance	scalar	*Visual	NORML	NORML		
	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history
	Visc @ 40°C	cSt	ASTM D445	;	52.4		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Meta	ls		April 224			
1000037 10	Viscosity @ 40°C			Acid Number (ng 100 Mumber (ng 200 M	Acid Number		
. :	: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : UCH06153226 Received : 18 Apr 2024 : 06153226 Tested : 19 Apr 2024						R SOLUTIO CLAY AVE (ND RAPIDS,
ber :	: 10983304 : IND 2	Diagr		2 Apr 2024 - Dor	n Baldridge	Contact: KEV	US 49

To discuss this sample report, con * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCMICGRA [WUSCAR] 06153226 (Generated: 04/23/2024 15:48:26) Rev: 1

Certificate L2367

Contact/Location: KEVIN GEERTMAN - UCMICGRA

F: (616)531-0084

T: