

OIL ANALYSIS REPORT

Area ROTO XTEND [SVO-060003] **ATLAS COPCO API633070 - RADIAC ABRASIVES**

Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




Sample Rating Trend


| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
|------------------|---------------|-------------|------------|-------------|-------------|----------|
| Sample Number | | Client Info | | UCH06154511 | UCH05772960 | |
| Sample Date | | Client Info | | 25 Mar 2024 | 08 Feb 2023 | |
| Machine Age | hrs | Client Info | | 15819 | 9374 | |
| Oil Age | hrs | Client Info | | 4219 | 0 | |
| Oil Changed | | Client Info | | Not Changd | Not Changd | |
| Sample Status | | | | NORMAL | NORMAL | |
| CONTAMINATION | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | NEG | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | 1 | |
| Chromium | ppm | ASTM D5185m | >5 | <1 | 0 | |
| Nickel | ppm | ASTM D5185m | | 0 | 0 | |
| Titanium | ppm | ASTM D5185m | | <1 | 0 | |
| Silver | ppm | ASTM D5185m | | <1 | 0 | |
| Aluminum | ppm | ASTM D5185m | >15 | 1 | 0 | |
| Lead | ppm | ASTM D5185m | >65 | <1 | 0 | |
| Copper | ppm | ASTM D5185m | >65 | 4 | <1 | |
| Tin | ppm | ASTM D5185m | >10 | <1 | 0 | |
| Vanadium | ppm | ASTM D5185m | | <1 | 0 | |
| Cadmium | ppm | ASTM D5185m | | <1 | 0 | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | |
| Barium | ppm | ASTM D5185m | | 2 | 0 | |
| Molybdenum | ppm | ASTM D5185m | | 0 | 0 | |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | |
| Magnesium | ppm | ASTM D5185m | | <1 | <1 | |
| Calcium | ppm | ASTM D5185m | | 3 | <1 | |
| Phosphorus | ppm | ASTM D5185m | | 46 | 15 | |
| Zinc | ppm | ASTM D5185m | | 2 | 40 | |
| Sulfur | ppm | ASTM D5185m | | 61 | 23 | |
| CONTAMINANTS | 5 | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >35 | <1 | 0 | |
| Sodium | ppm | ASTM D5185m | | 2 | 7 | |
| Potassium | ppm | ASTM D5185m | >20 | 2 | 1 | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | 0.14 | 0.63 | 0.39 | |



OIL ANALYSIS REPORT

VISUAL





| White Metal | scalar | *Visual | NONE | NONE | NONE | |
|-------------------------------------------------------------------------------|-------------------------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------------------------------------------------------|------------------------------------------------|
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | |
| Silt | scalar | *Visual | NONE | NONE | NONE | |
| Debris | scalar | *Visual | NONE | NONE | NONE | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | |
| Appearance | scalar | *Visual | NORML | NORML | NORML | |
| Odor | scalar | *Visual | NORML | NORML | NORML | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | NEG | |
| Free Water | scalar | *Visual | | NEG | NEG | |
| FLUID PROPERT | IES | method | limit/base | current | history1 | history |
| Visc @ 40°C | cSt | ASTM D445 | 46 | 49.3 | 49.5 | |
| SAMPLE IMAGES | \$ | method | limit/base | current | history1 | history |
| Color | | | | | | no image |
| Bottom | | | | | | no image |
| udd 2+ 0 ECCe 9 H | | | Mar25/24 | | | |
| Non-ferrous Metals | 5 | | Mar25/24 | | | |
| Viscosity @ 40°C | | | W | Acid Number | | |
| 55 Abnormal | | | | | | |
| - | | | 0.8 0.6 0.6 0.4 0.4 0.4 Viumpet War Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Viumpet Vi | 0 - | | |
| () 50 () 0 () 0 () 0 () 0 () 0 () 0 () 0 () | | | ມີ ພູ່ມີ 0.4 | 0 | | |
| 8 45 - | | | dumbe | Processor | | |
| Abnormal | | | 2 U.Z | Base | | |
| 40 L + | | | | 10 | | |
| Feb8/23 | | | Mar25/24 | Feb 8/23 | | |
| : WearCheck USA - 501 : UCH06154511 : 06154511 : 10989934 : IND 2 | l Madiso Recei Teste Diagn | ved : 19 d : 22 | v, NC 27513 9 Apr 2024 2 Apr 2024 8 Apr 2024 - Se | ean Felton | N HENRY FOSTI 4700 LEBOUF SAII ontact: RACHEL | rget stre Nt Louis, I Us 63 ⁻ |

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Contact/Location: RACHEL VON HATTEN - UCJOHSAI

Page 2 of 2

rvonhatten@jhf.com T: (314)593-1267

F: (314)874-0965