

OIL ANALYSIS REPORT

Area [217061] **TSP** 130 16686

Gearbox

7 460 (--- GAL)

Sample Rating Trend



Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC06154594		
Sample Date		Client Info		09 Apr 2024		
Machine Age	hrs	Client Info		2015		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	٧	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	4		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>50	<1		
Copper	ppm	ASTM D5185m	>200	<1		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		1		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		<1		
Phosphorus	ppm	ASTM D5185m		281		
Zinc	ppm	ASTM D5185m		22		
Sulfur	ppm	ASTM D5185m		12780		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<1		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.99		



200 150

OIL ANALYSIS REPORT



VISUAL		method	limit/base	current	history1	history2		
White Metal	scalar	*Visual	NONE	NONE				
Yellow Metal	scalar	*Visual	NONE	NONE				
Precipitate	scalar	*Visual	NONE	NONE				
Silt	scalar	*Visual	NONE	NONE				
Debris	scalar	*Visual	NONE	NONE				
Sand/Dirt	scalar	*Visual	NONE	NONE				
Appearance	scalar	*Visual	NORML	NORML				
Odor	scalar	*Visual	NORML	NORML				
Emulsified Water	scalar	*Visual	>0.2	NEG				
Free Water	scalar	*Visual		NEG				
FLUID PROPERT	TES	method	limit/base	current	history1	history2		
Visc @ 40°C	cSt	ASTM D445		449				
SAMPLE IMAGES	6	method	limit/base	current	history1	history2		
Color				no image	no image	no image		
Bottom				no image	no image	no image		
GRAPHS								
Iron (ppm)				Lead (ppm)				
Severe			20	Severe				
400 Abnormal			퉅10	Abnormal				
0				0				
Apr9/24			Apr9/24	Apr9/24		Apr9/24		
Aluminum (ppm)								
Severe	2				30 T Severe			
Abnormal			돌 ²	Abnormal				
Apr9/24			Apr9/24	Apr9/24		Apr9/24		
Copper (ppm)	Silicon (ppm)							
600 Severe			15	0				
400 Abnormal			E 10	· [
O Apr9/24			Apr9/24	Apr9/24		Apr9/24		
Viscosity @ 40°C				Acid Number				
600 T -:			Acid Number (mg KOH/g)	0				
400 - Abnamal			.0.	5				
0			Num 0	0				
24			24 -	24		24		





Certificate 12367

Laboratory Sample No.

: WC06154594 Lab Number : 06154594

Unique Number : 10990017 Test Package : MOB 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 19 Apr 2024

Tested : 22 Apr 2024 Diagnosed : 23 Apr 2024 - Don Baldridge

P.O. Box 19567

US 30325 Contact: JOHN STEED john.steed@momar.com

MOMAR Incorporated

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (404)355-4580 F: (678)894-4204

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) Report Id: MOMATL [WUSCAR] 06154594 (Generated: 04/23/2024 18:15:56) Rev: 1

Contact/Location: JOHN STEED - MOMATL

Atlanta, GA