

OIL ANALYSIS REPORT

Sample Rating Trend





Machine Id MACK 20139

Component Natural Gas Engine

Fluid PETRO CANADA 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		SBP0007389		
Sample Date		Client Info		17 Apr 2024		
Machine Age	hrs	Client Info		8214		
Oil Age	hrs	Client Info		514		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	10		
Chromium	ppm	ASTM D5185m	>5	<1		
Nickel	ppm	ASTM D5185m	>4	<1		
Titanium	ppm	ASTM D5185m	>5	<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>150	<1		
Tin	ppm	ASTM D5185m	>4	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method				history2
Boron	ppm	Method ASTM D5185m	limit/base	current 9	history1	history2
	ppm ppm		limit/base			
Boron Barium		ASTM D5185m	limit/base	9		
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m	limit/base	9 0		
Boron Barium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56		
Boron Barium Molybdenum Manganese	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56 <1		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56 <1 529		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56 <1 529 1674	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56 <1 529 1674 737	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56 <1 529 1674 737 982		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56 <1 529 1674 737 982 2587		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	9 0 56 <1 529 1674 737 982 2587 current		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base >25	9 0 56 <1 529 1674 737 982 2587 2587 current 5		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m	limit/base >25	9 0 56 <1 529 1674 737 982 2587 <u>current</u> 5 2		
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base >25 >20	9 0 56 <1 529 1674 737 982 2587 current 5 2 2	 history1 	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base >25 >20 limit/base	9 0 56 <1 529 1674 737 982 2587 current 5 2 2 2 2 2 2	 history1 history1	 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base >25 >20 limit/base	9 0 56 <1 529 1674 737 982 2587 <u>current</u> 5 2 2 2 2 2 2 <u>current</u> 0	 history1 history1 history1	 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base >25 >20 limit/base	9 0 56 <1 529 1674 737 982 2587 <i>current</i> 5 2 2 2 2 <i>current</i> 0 10.8	 history1 history1 history1	 history2 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base >25 >20 limit/base >20 s20	9 0 56 <1 529 1674 737 982 2587 <u>current</u> 5 2 2 2 2 2 <u>current</u> 0 10.8 21.0	 history1 history1 history1	history2 history2 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D7844 *ASTM D7624	limit/base >25 >20 limit/base >20 >30 limit/base	9 0 56 <1 529 1674 737 982 2587 current 5 2 2 2 2 current 0 10.8 21.0 current	history1 history1 history1 history1 history1	 history2 history2 history2 history2



OIL ANALYSIS REPORT

FT-IR (Direct Trend)	VISUAL		method	limit/base	current	history1	history2
Oxidation	White Metal	scalar	*Visual	NONE	NONE		
sussesses Sulfation	Yellow Metal	scalar	*Visual	NONE	NONE		
E 25 Abnormal	Precipitate	scalar	*Visual	NONE	NONE		
²⁹ 20	Silt	scalar	*Visual	NONE	NONE		
15	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
10	Appearance	scalar	*Visual	NORML	NORML		
Apri17/24 Apri17/24	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
Base Number	Free Water	scalar	*Visual	20.1	NEG		
	FLUID PROPER		method	limit/base	current	history1	history2
(역 4.0-) (외 말 3.0-	Visc @ 100°C	cSt	ASTM D445	mmbase	14.8		
ang 2.0 -	GRAPHS						
₹ 8 1.0							
	Ferrous Alloys						
24 0.0	iron						
Apri 1/24 A r c - r A	8 - nickel						
	6 -						
Viscosity @ 100°C	mdd						
19	4-						
17 Abnormal	2						
©16 0015							
0) 15- 73 14-	04						
13 Abnormal	Apr17/24			Apr17/24			
12				Ar			
11	Non-ferrous Met	als					
April 1/24	copper						
₹ 4	8 - enseense lead						
	6 -						
	m dd						
	4						
	2						
	or17/24			or17/2			
	¥			Ar			
	Viscosity @ 100°		Base Number				
	18		5.0	 			
	Abnormal			<u>~</u> 4.0			
				KOH/6			
	()-16 			.0.9 (B) KK (UHQ) (J) J) J			
	tg 14			 	1		
	13 - Abnormal			ase N			
	12 -			^{°°} 1.0•			
	11						
	Apr17/24			Apr17/24	Apr17/24		Apr17/24
	Apr			Apr	Api		Apr
	r : 06155165 r : 10990588 e : FLEET rt, contact Customer Sei	Recei Teste Diagr	ved : 19 d : 22 nosed : 22	9 Apr 2024 2 Apr 2024 2 Apr 2024 - We 9.	es Davis		02 N 16TH ST OMAHA, NE US 68110 : TROY BEAN
Statements of conformity to					rule (JCGM 106	:2012)	F:
Statements of comorning to		511 118 5111	ιριο αυστρία				

Report Id: FCCOMA [WUSCAR] 06155165 (Generated: 04/23/2024 01:57:25) Rev: 1

Submitted By: TROY BEAN

Page 2 of 2