

## **OIL ANALYSIS REPORT**

Sample Rating Trend





[W/O 10612] VOLVO A30G 752750

Component Hydraulic System Fluid VOLVO SUPER HYDRAULIC OIL 46 (35 GAL)

## DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Area

### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	<b>MATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		ML0001160		
Sample Date		Client Info		10 Apr 2024		
Machine Age	hrs	Client Info		1823		
Oil Age	hrs	Client Info		1823		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	11		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	2		
Lead	ppm	ASTM D5185m	>20	2		
Copper	ppm	ASTM D5185m	>150	4		
Tin	ppm	ASTM D5185m	>20	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	14	0		
Barium	ppm	ASTM D5185m	0.0	0		
Molybdenum	ppm	ASTM D5185m	0.0	<1		
Manganese	ppm	ASTM D5185m	0.0	0		
Magnesium	ppm	ASTM D5185m	2.6	3		
Calcium	ppm	ASTM D5185m	49	105		
Phosphorus	ppm	ASTM D5185m	354	354		
Zinc	ppm	ASTM D5185m	419	444		
Sulfur	ppm	ASTM D5185m	3719	2420		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m		2		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		6908		
Particles >6µm		ASTM D7647	>5000	760		
Particles >14µm		ASTM D7647	>160	51		
Particles >21µm		ASTM D7647	>40	8		
Particles >38µm		ASTM D7647	>10	0		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>/19/14	20/17/13		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.42		
0:01:27) Rev: 1		2000			mitted By: DEL	


Report Id: VOLVO0150 [WUSCAR] 06155184 (Generated: 04/24/2024 10:01:27) Rev: 1


Submitted By: DELANO GREGORY Page 1 of 2



# **OIL ANALYSIS REPORT**







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPER	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	43.5		
SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Color				•	no image	no image
Bottom					no image	no image
GRAPHS						
Ferrous Alloys				Particle Cour	nt	
5 iron			491,52	, I		T <sup>26</sup>
0 - nickel			122,88	-		-24
			30,72			22
5-			30,72	1		-22
			7,68			-20
Apr1 0/24			Apr10/24 (per 1 ml)		N	-18 -18 -14 -14
Apr			April0/24 156'1 ml) 151'1 April 0/24			
Non-ferrous Meta	ls		pitred 481			-16
Copper			ja 12		<b>``</b>	-14
8 assessment lead			quint			
4			31	)-		-12
2				Bisresemal		-10
0	*****		*******	T		
Apr10/24			Apr10/24	2		+8
Apr			Apr	4μ 6μ	1 2	6
Viscosity @ 40°C				<sup>4μ 6μ</sup> Acid Number	14µ 21µ	38µ 71µ
Abnormal			€0.50			
0+ 9			(0,5/ (0,4/ ) ) ) (0,1/ ) ) (0,1/) (0,1/)	)+		
5 - Base			ຍັ 0.30	]		
			- e 0.2	1		
Abnormal				1		
54			0.00			v C
Apr10/24			Apr10/24	Apr10/24		ACO Luck
-			-	-		
VearCheck USA - 50 /IL0001160 / <mark>6155184</mark>	Rece Teste	ived : 19 ed : 24	9 Apr 2024 1 Apr 2024	460	<b>IG-LOGAN EQUIPMEN</b> 1 WASHINGTON BA	I BOULEVARI LTIMORE, MI
0990607	Diagr	nosed : 24	Apr 2024 - Jonat	han Hester		US 2122
ONST	ion at t	000 007 400	n		Contact: DELA	
ntact Customer Serv					dgregory@mccl	ung-logan.cor T

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (410)242-7835

Certificate L2367

Laboratory

Sample No. Lab Number Unique Number Test Package

Submitted By: DELANO GREGORY

Т: