


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

GOODYEAR AKRON TEST 103

Hydraulic System

CONOCO MEGAFLOW AW 46 (--- GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor. Due to an abnormal test result it is recommended to contact Stauff Corp at (201)-444-7800 for help resolving the issue.

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Jan 2023	Apr2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		ST46354	ST44378	
Sample Date		Client Info		21 Apr 2024	02 Jan 2023	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed	1110	Client Info		N/A	N/A	
Sample Status		Onoric iriio		ABNORMAL	ABNORMAL	
-			11 11 11			111
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0	<1	
Chromium	ppm	ASTM D5185m	>20	0	0	
Nickel	ppm	ASTM D5185m	>20	0	0	
Titanium	ppm	ASTM D5185m		<1	0	
Silver	ppm	ASTM D5185m	0.0	0	0	
Aluminum	ppm	ASTM D5185m	>20	0	0	
Lead	ppm	ASTM D5185m	>20	0	0	
Copper	ppm	ASTM D5185m	>20	1	3	
Tin	ppm	ASTM D5185m	>20	0	0	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m		<1	0	
Calcium	ppm	ASTM D5185m		54	52	
Phosphorus	ppm	ASTM D5185m		287	261	
Zinc	ppm	ASTM D5185m		377	279	
Sulfur	ppm	ASTM D5185m		937	741	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	
Sodium	ppm	ASTM D5185m		0	2	
Potassium	ppm	ASTM D5185m	>20	0	0	
Water	%	ASTM D6304	>0.05	0.002	0.006	
ppm Water	ppm	ASTM D6304	>500	20	65.6	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>640	46731	▲ 59035	
Particles >6µm		ASTM D7647	>160	<u> </u>	<u>▲</u> 13858	
Particles >14µm		ASTM D7647	>20	332	△ 573	
Particles >21μm		ASTM D7647	>4	^ 64	<u> 119</u>	
Particles >38µm		ASTM D7647	>3	1	<u> 5</u>	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>16/14/11	23/20/16	△ 23/21/16	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
A ! I N	1/011/	AOTH DOOLS	0.00	0.25	0.00	

Acid Number (AN)

0.28

0.35

mg KOH/g ASTM D8045 0.38



OIL ANALYSIS REPORT



Received

Tested

: 22 Apr 2024

: 23 Apr 2024

: 24 Apr 2024 - Jonathan Hester





Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

: ST46354 Lab Number : 06155968

Unique Number: 10991391

Diagnosed Test Package : IND 2 (Additional Tests: KF)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

FLUID POWER SOLUTIONS

4400 Edgewyn Ave. Hilliard, OH US 43026

Contact: SCOTT ROGERS srogers@fluid-power-solutions.com

T: (614)777-8954

F: (614)777-8640 Contact/Location: SCOTT ROGERS - FLUHIL