

FUEL REPORT

Sample Rating Trend

NORMAL

Machine Id

SRASOTA COUNTY - CENTRAL

Bulk Tank Diesel Fuel

Fluid No.2 DIESEL FUEL (ULTRALOW SULPHUR) (5

DIAGNOSIS

Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel.

Corrosion

All metal levels are normal indicating no corrosion in the system.

Contaminants

The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample. There is no indication of any contamination in the fuel.


Fuel Condition


Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.


| L CO WWT | P T4 | | | | | |
|---------------|--------|-------------|------------|-------------|----------|----------|
| i) (5000 GAL) | | | | Apr2024 | | |
| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WCDF4588 | | |
| Sample Date | | Client Info | | 16 Apr 2024 | | |
| Machine Age | mls | Client Info | | 0 | | |
| Sample Status | | | | NORMAL | | |
| PHYSICAL PROP | ERTIES | method | limit/base | current | history1 | history2 |
| ASTM Color | scalar | *ASTM D1500 | | L4.5 | | |
| Visc @ 40°C | cSt | ASTM D445 | 3.0 | 2.57 | | |
| SULFUR CONTEI | NT | method | limit/base | current | history1 | history2 |
| Sulfur | ppm | ASTM D5185m | 10 | 0 | | |
| Sulfur (UVF) | ppm | ASTM D5453 | | 11 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | <1.0 | 4 | | |
| Sodium | ppm | ASTM D5185m | <0.1 | 4 <1 | | |
| Potassium | ppm | ASTM D5185m | <0.1 | 0 | | |
| Vater | % | ASTM D6304 | | 0.004 | | |
| opm Water | ppm | ASTM D6304 | <500 | 40 | | |
| % Gasoline | % | *In-House | < 0.50 | 0.0 | | |
| % Biodiesel | % | *In-House | <20.0 | 2.0 | | |
| HEAVY METALS | | method | limit/base | current | history1 | history2 |
| Aluminum | ppm | ASTM D5185m | <0.1 | 0 | | |
| Nickel | ppm | ASTM D5185m | <0.1 | 0 | | |
| _ead | ppm | ASTM D5185m | <0.1 | 0 | | |
| /anadium | ppm | ASTM D5185m | <0.1 | <1 | | |
| ron | ppm | ASTM D5185m | <0.1 | 0 | | |
| Calcium | ppm | ASTM D5185m | <0.1 | 0 | | |
| Magnesium | ppm | ASTM D5185m | <0.1 | 0 | | |
| Phosphorus | ppm | ASTM D5185m | <0.1 | 0 | | |
| Zinc | ppm | ASTM D5185m | <0.1 | 0 | | |
| SAMPLE IMAGES | \$ | method | limit/base | current | history1 | history2 |
| Color | | | | | no image | no image |
| Bottom | | | | | no image | no image |



FUEL REPORT







Contact/Location: 321-285-8878 X1 - WENDALL STRODERD - TANPAL