

OIL ANALYSIS REPORT

SAMPLE INFORMATION method

Sample Rating Trend

limit/base



history1

current

history2

Machine Id

5844777 (S/N 1324)

Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

SAMPLE INFURI	VIATION	method	iimit/base	current	nistory i	nistory2
Sample Number		Client Info		KCPA016588	KCP33635	KCP20734
Sample Date		Client Info		18 Apr 2024	27 Apr 2021	24 Apr 2020
Machine Age	hrs	Client Info		15508	8881	6822
Oil Age	hrs	Client Info		0	0	3000
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				ABNORMAL	ABNORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	<1
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	<1	<1	<1
Titanium	ppm	ASTM D5185m	>3	<1	<1	0
Silver	ppm	ASTM D5185m	>2	<1	<1	0
Aluminum	ppm	ASTM D5185m	>10	3	2	0
Lead	ppm	ASTM D5185m	>10	<1	<1	<1
Copper	ppm	ASTM D5185m	>50	11	13	15
Tin	ppm	ASTM D5185m	>10	<1	<1	<1
Antimony	ppm	ASTM D5185m			0	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	10	1
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		<1	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	90	<1	3	1
Calcium	ppm	ASTM D5185m	2	0	4	0
Phosphorus	ppm	ASTM D5185m		0	0	4
Zinc	ppm	ASTM D5185m		0	41	58
Sulfur	ppm	ASTM D5185m		17152	14777	16003
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	<1
Sodium	ppm	ASTM D5185m		0	3	2
Potassium	ppm	ASTM D5185m	>20	2	<1	<1
Water	%	ASTM D6304	>0.05	0.008	0 .169	0.010
ppm Water	ppm	ASTM D6304	>500	85	▲ 1690	104.6
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647				5354
Particles >6µm		ASTM D7647	>1300			1558
Particles >14µm		ASTM D7647	>80			78
Particles >21µm		ASTM D7647	>20			21
Particles >38µm		ASTM D7647	>4			2
Particles >71µm		ASTM D7647	>3			0
Oil Cleanliness		ISO 4406 (c)	>/17/13			18/13
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN) 49:46) Bey: 1	mg KOH/g	ASTM D8045	0.4	0.41	0.345 on: Service Mar	0.311

Report Id: SLOAUS [WUSCAR] 06156943 (Generated: 04/24/2024 18:49:46) Rev: 1

Contact/Location: Service Manager - SLOAUS




Abnorma

40

38 Apr24/20

OIL ANALYSIS REPORT


Water (K	(F)	
10000 Severe		
€ 8000-		
(E 8000 ap 6000 4000		
≥ 4000	1	
2000 Abnormal		
Apr24/20	Apr27/21	Apr18/24 -
Water (K	(F)	
10000 - Severe		




Apr27/21

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	A MODER	🔺 MODER	VLITE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	▲ 1.0	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	44.1	43.7	43.9
SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Color				A.		
					Sugar and a star	1/2

Bottom





Certificate 12367

Contact/Location: Service Manager - SLOAUS Page 2 of 2

F: