


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# 5940580 (S/N 1223)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

#### Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

|                 |        | 1            | Oct2021    | Apr2024     |             |          |
|-----------------|--------|--------------|------------|-------------|-------------|----------|
| SAMPLE INFORM   | MATION | method       | limit/base | current     | history1    | history2 |
| Sample Number   |        | Client Info  |            | KCPA013708  | KCP39137    |          |
| Sample Date     |        | Client Info  |            | 17 Apr 2024 | 06 Oct 2021 |          |
| Machine Age     | hrs    | Client Info  |            | 41066       | 27207       |          |
| Oil Age         | hrs    | Client Info  |            | 2358        | 0           |          |
| Oil Changed     |        | Client Info  |            | Changed     | Changed     |          |
| Sample Status   |        |              |            | ATTENTION   | ATTENTION   |          |
| WEAR METALS     |        | method       | limit/base | current     | history1    | history2 |
| Iron            | ppm    | ASTM D5185m  | >50        | 0           | <1          |          |
| Chromium        | ppm    | ASTM D5185m  | >10        | <1          | 0           |          |
| Nickel          | ppm    | ASTM D5185m  | >3         | <1          | <1          |          |
| Titanium        | ppm    | ASTM D5185m  | >3         | <1          | 0           |          |
| Silver          | ppm    | ASTM D5185m  | >2         | <1          | <1          |          |
| Aluminum        | ppm    | ASTM D5185m  | >10        | 3           | <1          |          |
| Lead            | ppm    | ASTM D5185m  | >10        | <1          | 0           |          |
| Copper          | ppm    | ASTM D5185m  | >50        | 5           | 7           |          |
| Tin             | ppm    | ASTM D5185m  | >10        | <1          | <1          |          |
| Antimony        | ppm    | ASTM D5185m  |            |             | <1          |          |
| Vanadium        | ppm    | ASTM D5185m  |            | <1          | 0           |          |
| Cadmium         | ppm    | ASTM D5185m  |            | <1          | 0           |          |
| ADDITIVES       |        | method       | limit/base | current     | history1    | history2 |
| Boron           | ppm    | ASTM D5185m  | 0          | 0           | 5           |          |
| Barium          | ppm    | ASTM D5185m  | 90         | 0           | 0           |          |
| Molybdenum      | ppm    | ASTM D5185m  | 0          | <1          | 0           |          |
| Manganese       | ppm    | ASTM D5185m  |            | <1          | 0           |          |
| Magnesium       | ppm    | ASTM D5185m  | 100        | 3           | <1          |          |
| Calcium         | ppm    | ASTM D5185m  | 0          | 0           | 0           |          |
| Phosphorus      | ppm    | ASTM D5185m  | 0          | 0           | 2           |          |
| Zinc            | ppm    | ASTM D5185m  | 0          | 0           | 0           |          |
| Sulfur          | ppm    | ASTM D5185m  | 23500      | 21048       | 14337       |          |
| CONTAMINANTS    | ;      | method       | limit/base | current     | history1    | history2 |
| Silicon         | ppm    | ASTM D5185m  | >25        | 1           | <1          |          |
| Sodium          | ppm    | ASTM D5185m  |            | 0           | 0           |          |
| Potassium       | ppm    | ASTM D5185m  | >20        | 2           | <1          |          |
| Water           | %      | ASTM D6304   | >0.05      | 0.008       | 0.008       |          |
| ppm Water       | ppm    | ASTM D6304   | >500       | 88          | 82.3        |          |
| FLUID CLEANLIN  | IESS   | method       | limit/base | current     | history1    | history2 |
| Particles >4µm  |        | ASTM D7647   |            | 6104        | 1984        |          |
| Particles >6µm  |        | ASTM D7647   | >1300      | <b>1449</b> | 655         |          |
| Particles >14μm |        | ASTM D7647   | >80        | 99          | 85          |          |
| Particles >21µm |        | ASTM D7647   | >20        | 24          | 21          |          |
| Particles >38µm |        | ASTM D7647   | >4         | 1           | 0           |          |
| Particles >71µm |        | ASTM D7647   | >3         | 0           | 0           |          |
| Oil Cleanliness |        | ISO 4406 (c) | >/17/13    | 0 20/18/14  | 17/14       |          |
| FLUID DEGRADA   | TION   | method       | limit/base | current     | history1    | history2 |

Acid Number (AN)

mg KOH/g ASTM D8045 1.0

0.551

0.45

Contact/Location: Service Manager - ALGOAKCA



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

: KCPA013708 Lab Number : 06156946 Unique Number : 10992369

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 22 Apr 2024 **Tested** : 24 Apr 2024 Diagnosed : 24 Apr 2024 - Angela Borella

Test Package : IND 2 ( Additional Tests: KF, PrtCount )

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: ALGOAKCA [WUSCAR] 06156946 (Generated: 04/24/2024 17:55:19) Rev: 1

Contact/Location: Service Manager - ALGOAKCA

547 W YOSEMITE AVE

Contact: Service Manager

OAKDALE, CA

US 95361

T:

F: