


# **OIL ANALYSIS REPORT**





## **DIAGNOSIS**

#### Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

### Contamination

There is a high amount of particulates present in the oil.


### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				Apr2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06156977		
Sample Date		Client Info		22 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
					HISTORY	HIStory
Iron	ppm	ASTM D5185m	>200	53		
Chromium	ppm		>15	<1		
Nickel	ppm	ASTM D5185m	>15	<1		
Titanium	ppm	ASTM D5185m		1		
Silver	ppm	ASTM D5185m		<1		
Aluminum	ppm	ASTM D5185m		3		
Lead	ppm	ASTM D5185m	>100	<1		
Copper	ppm	ASTM D5185m	>200	<1		
Tin	ppm	ASTM D5185m	>25	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		1		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		6		
Phosphorus	ppm	ASTM D5185m		624		
Zinc	ppm	ASTM D5185m		5		
Sulfur	ppm	ASTM D5185m		989		
CONTAMINANTS		method	limit/base	current	history1	history2
					Thotory I	motory
Silicon	ppm		>50	8		
Sodium	ppm	ASTM D5185m	00	0		
Potassium	ppm	ASTM D5185m	>20	2		
Water	%	ASTM D6304	>0.2	0.00		
ppm Water	ppm	ASTM D6304	>2000	0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	<u> </u>		
Particles >6µm		ASTM D7647	>5000	<u>A</u> 85105		
Particles >14μm		ASTM D7647	>640	<b>4424</b>		
Particles >21µm		ASTM D7647	>160	<u>▲</u> 592		
Particles >38μm		ASTM D7647	>40	20		
Particles >71µm		ASTM D7647	>10	2		
Oil Cleanliness		ISO 4406 (c)	>21/19/16	<u>4</u> 24/24/19		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.17		



# **OIL ANALYSIS REPORT**





Certificate 12367

Laboratory Sample No.

Lab Number : 06156977 Unique Number : 10992400

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : UCH06156977 Received

: 22 Apr 2024 **Tested** Diagnosed

: 23 Apr 2024 : 25 Apr 2024 - Jonathan Hester 110 ELMGROVE PARK ROCHESTER, NY US 14624

Contact: DAVE HUNGARTER

**CORROSION PRODUCTS & EQUIPMENT INC** 

Test Package : IND 2 ( Additional Tests: KF, PrtCount ) To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (585)247-3030 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: (585)247-7268

Contact/Location: DAVE HUNGARTER - UCCORROC