


# **OIL ANALYSIS REPORT**

# **NOT GIVEN [268981]** PNEUTECH AK100021209 - KEHE

Component Compressor



## Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

## Contamination

There is no indication of any contamination in the


## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| SAMPLE INFORM    | MATION   | method      | limit/base | current     | history1 | history2 |
|------------------|----------|-------------|------------|-------------|----------|----------|
| Sample Number    |          | Client Info |            | UFD0000772  |          |          |
| Sample Date      |          | Client Info |            | 14 Mar 2024 |          |          |
| Machine Age      | hrs      | Client Info |            | 0           |          |          |
| Oil Age          | hrs      | Client Info |            | 0           |          |          |
| Oil Changed      |          | Client Info |            | Changed     |          |          |
| Sample Status    |          |             |            | NORMAL      |          |          |
| CONTAMINATION    | V        | method      | limit/base | current     | history1 | history2 |
| Water            |          | WC Method   | >0.1       | NEG         |          |          |
| WEAR METALS      |          | method      | limit/base | current     | history1 | history2 |
| Iron             | ppm      | ASTM D5185m | >50        | 0           |          |          |
| Chromium         | ppm      | ASTM D5185m | >10        | <1          |          |          |
| Nickel           | ppm      | ASTM D5185m |            | 0           |          |          |
| Titanium         | ppm      | ASTM D5185m |            | 0           |          |          |
| Silver           | ppm      | ASTM D5185m |            | 0           |          |          |
| Aluminum         | ppm      | ASTM D5185m | >25        | 0           |          |          |
| Lead             | ppm      | ASTM D5185m | >25        | 0           |          |          |
| Copper           | ppm      | ASTM D5185m | >50        | 0           |          |          |
| Tin              | ppm      | ASTM D5185m | >15        | <1          |          |          |
| Vanadium         | ppm      | ASTM D5185m |            | 0           |          |          |
| Cadmium          | ppm      | ASTM D5185m |            | 0           |          |          |
| ADDITIVES        |          | method      | limit/base | current     | history1 | history2 |
| Boron            | ppm      | ASTM D5185m |            | 0           |          |          |
| Barium           | ppm      | ASTM D5185m |            | 0           |          |          |
| Molybdenum       | ppm      | ASTM D5185m |            | 0           |          |          |
| Manganese        | ppm      | ASTM D5185m |            | 0           |          |          |
| Magnesium        | ppm      | ASTM D5185m |            | <1          |          |          |
| Calcium          | ppm      | ASTM D5185m |            | <1          |          |          |
| Phosphorus       | ppm      | ASTM D5185m |            | 40          |          |          |
| Zinc             | ppm      | ASTM D5185m |            | 0           |          |          |
| Sulfur           | ppm      | ASTM D5185m |            | 455         |          |          |
| CONTAMINANTS     | ;        | method      | limit/base | current     | history1 | history2 |
| Silicon          | ppm      | ASTM D5185m | >25        | 6           |          |          |
| Sodium           | ppm      | ASTM D5185m |            | 2           |          |          |
| Potassium        | ppm      | ASTM D5185m | >20        | <1          |          |          |
| FLUID DEGRADA    | TION     | method      | limit/base | current     | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045  |            | 0.062       |          |          |



## **OIL ANALYSIS REPORT**




| VISUAL                  |        | method    | limit/base | current | history1 | history2 |
|-------------------------|--------|-----------|------------|---------|----------|----------|
| White Metal             | scalar | *Visual   | NONE       | NONE    |          |          |
| Yellow Metal            | scalar | *Visual   | NONE       | NONE    |          |          |
| Precipitate             | scalar | *Visual   | NONE       | NONE    |          |          |
| Silt                    | scalar | *Visual   | NONE       | NONE    |          |          |
| Debris                  | scalar | *Visual   | NONE       | NONE    |          |          |
| Sand/Dirt               | scalar | *Visual   | NONE       | NONE    |          |          |
| Appearance              | scalar | *Visual   | NORML      | NORML   |          |          |
| Odor                    | scalar | *Visual   | NORML      | NORML   |          |          |
| <b>Emulsified Water</b> | scalar | *Visual   | >0.1       | NEG     |          |          |
| Free Water              | scalar | *Visual   |            | NEG     |          |          |
| FLUID PROPERT           | ΓIES   | method    | limit/base | current | history1 | history2 |
| Visc @ 40°C             | cSt    | ASTM D445 |            | 43.9    |          |          |


| SAMPLE IMAGES | method | limit/base | current | history1 | history2 |
|---------------|--------|------------|---------|----------|----------|
| Color         |        |            |         | no image | no image |
| Bottom        |        |            |         | no image | no image |

# Ferrous Alloys

**GRAPHS** 











Certificate 12367

Laboratory

Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Sample No. : UFD0000772 Lab Number : 06157032

Unique Number : 10992455

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Received : 22 Apr 2024 Tested

: 24 Apr 2024 Diagnosed

: 25 Apr 2024 - Jonathan Hester

US 60193 Contact: ED DIENER ed.diener@fluidairedynamics.com T: (847)678-8388

**FLUID-AIRE DYNAMICS** 

550 ALBION AVE

SCHAUMBURG, IL

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)