

## **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

## Area **PG 46 [279246] IT200112 - HARBOR MANF** Component

Component Compressor

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0000755		
Sample Date		Client Info		01 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	۷	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	0		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		255		
Zinc	ppm	ASTM D5185m		116		
Sulfur	ppm	ASTM D5185m		29		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.40		



# **OIL ANALYSIS REPORT**





	White Metal	scalar	*Visual	NONE	NONE			
	Yellow Metal	scalar	*Visual	NONE	NONE			
	Precipitate	scalar	*Visual	NONE	NONE			
	Silt	scalar	*Visual	NONE	NONE			
	Debris	scalar	*Visual	NONE	NONE			
	Sand/Dirt	scalar	*Visual	NONE	NONE			
Apr1/24	Appearance	scalar	*Visual	NORML	NORML			
Ap	Odor	scalar	*Visual	NORML	NORML			
	Emulsified Water	scalar	*Visual	>0.1	NEG			
	Free Water	scalar	*Visual		NEG			
	FLUID PROPERT		method	limit/base	current	history1	history2	
	Visc @ 40°C	cSt	ASTM D445	IIIIII/Dase	54.6	TIIStOLA	TIIStoryz	
	_							
	SAMPLE IMAGES	5	method	limit/base	current	history1	history2	
Apr1/24	Color					no image	no image	
	Bottom					no image	no image	
	2 0 +2/L/dW			Apr1/24				
	Non-ferrous Metal	5		Apri/24				
	Viscosity @ 40°C				A stal Alexandra a			
	<sup>60</sup> T			<u>_</u> 0.50	Acid Number			
	55- Abnormal			(b)H0,0.40 (b)H0,0.40 (c) 0.30 (c) 0.20 (c) 0.10 (c) 40 (c) 0.10 (c) 40 (c) 0.10 (c) 0.10 (c) 0.10 (c) 0.10 (c) 0.10 (c) 0.10 (c) 0.10 (c) 0.10 (c) 0.10 (c) 0.40 (c) 0.10 (c)				
	(고) 50 + <mark>Abnormal</mark> 정 45 + -			ຍິ 0.30	•			
	Alternational			- <sup>2</sup> 9 0.20	•			
	40 Abnormal			- <sup>2</sup> 0.10				
	35 +			0.00				
	Apr1/24			Apr1/24	Apr1/24			
	: UFD0000755	Recei	Madison Ave., Cary, NC 27513   Received : 22 Apr 2024   Tested : 23 Apr 2024   Diagnosed : 24 Apr 2024 - Sean Felton			FLUID-AIRE DYNAMIC 550 ALBION AV SCHAUMBURG, US 6019 Contact: ED DIENE		

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ED DIENER - UCFLUSCH

F: