

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area PG 46 [282637] Machine Id API588049 - DESLNUFIERS Component

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UFD0001156		
Sample Date		Client Info		03 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		2		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	0		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		5		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		43		
Zinc	ppm	ASTM D5185m		48		
Sulfur	ppm	ASTM D5185m		57		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.07		



OIL ANALYSIS REPORT

VISUAL





VISUAL		method			history1	history2	
White Metal	scalar	*Visual	NONE	NONE			
Yellow Metal	scalar	*Visual	NONE	NONE			
Precipitate	scalar	*Visual	NONE	NONE			
Silt	scalar	*Visual	NONE	NONE			
Debris	scalar	*Visual	NONE	NONE			
Sand/Dirt	scalar	*Visual	NONE	NONE			
Appearance	scalar	*Visual	NORML	NORML			
Odor	scalar	*Visual	NORML	NORML			
Emulsified Water	scalar	*Visual	>0.1	NEG			
Free Water	scalar	*Visual		NEG			
FLUID PROPER	TIES	method	limit/base	current	history1	history	
Visc @ 40°C	cSt	ASTM D44	5	46.6			
SAMPLE IMAGE	S	method	limit/base	current	history1	history	
Color					no image	no image	
Bottom					no image	no image	
Non-ferrous Meta	ls		Apr3/24				
Viscosity @ 40°C			Apr3/24	Acid Numb	er		
40 - Abnormal 			Apr3/24 -	Apr3/24			
: UFD0001156 r : 06157036 er : 10992459 e : IND 2	16157036 Tested : 23 Apr 2024 0992459 Diagnosed : 24 Apr 2024 - Sea				FLUID-AIRE DYNAMI 550 ALBION A SCHAUMBURG US 601 Contact: ED DIEN ed.diener@fluidairedynamics.c		

To discuss this sample report, co. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCFLUSCH [WUSCAR] 06157036 (Generated: 04/24/2024 16:18:14) Rev: 1

Certificate L2367

Contact/Location: ED DIENER - UCFLUSCH

F:

T: (847)678-8388