


OIL ANALYSIS REPORT

VACUUM PUMP

B70035 - Busch Vacuum Pump - Marlen 1

Vacuum Pump

BUSCH R-590 PUMP OIL (--- GAL)





Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0872488	WC0814168	WC0755368
Sample Date		Client Info		16 Apr 2024	18 Jul 2023	17 Apr 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				ATTENTION	ATTENTION	NORMAL
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>.1	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	<1	<1	<1
Chromium	ppm	ASTM D5185m	>20	<1	0	0
Nickel	ppm	ASTM D5185m	>20	<1	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	2	0	0
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>20	<1	0	0
Tin	ppm	ASTM D5185m	>20	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	2	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		<1	<1	<1
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		370	375	388
Zinc	ppm	ASTM D5185m		14	8	5
Sulfur	ppm	ASTM D5185m		383	421	407
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	1	2
Sodium	ppm	ASTM D5185m		0	0	0
Potassium	ppm	ASTM D5185m	>20	1	0	<1
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>5000	5514	5377	1767
Particles >6µm		ASTM D7647	>1300	1111	1743	481
Particles >14µm		ASTM D7647	>160	58	114	22
Particles >21µm		ASTM D7647	>40	13	22	4
Particles >38µm		ASTM D7647	>10	0	2	0
Particles >71μm		ASTM D7647		0	1	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	20/17/13	20/18/14	18/16/12
FLUID DEGRADA	TION					history2


0.18


0.23




OIL ANALYSIS REPORT










VISUAL						
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	120.8	116	110	111
SAMPLE IMAGES		method	limit/base	current	history1	history2









Certificate 12367

Sample No.

Laboratory

: WC0872488

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Lab Number : 06157673 **Tested** Unique Number : 10993096

Diagnosed Test Package : IND 2 (Additional Tests: PrtCount)

: 23 Apr 2024 : 24 Apr 2024

: 25 Apr 2024 - Angela Borella

OMAHA, NE US 68138 Contact: NEIL ARIANO njariano@hormel.com

PAPILLION FOODS

10808 S 132ND ST

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: