


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# KAESER CSD 125 4491879 (S/N 1282)

Component Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

### Recommendation

The oil change at the time of sampling has been noted. Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is a moderate amount of particulates present in the oil.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jun2014	Mar2019 Apr2021	Marž022 Novž022	Apr2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA012727	KCP53990	KCP52143
Sample Date		Client Info		16 Apr 2024	23 May 2023	21 Nov 2022
Machine Age	hrs	Client Info		35923	29034	25193
Oil Age	hrs	Client Info		5003	0	2200
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				ATTENTION	ABNORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	0
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	<1	0	<1
Titanium	ppm	ASTM D5185m	>3	<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	2	<1	0
Lead	ppm	ASTM D5185m	>10	<1	0	<1
Copper	ppm	ASTM D5185m	>50	8	9	8
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Vanadium	ppm	ASTM D5185m	-	0	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES	le le	method	limit/base	·	history1	history2
Boron	nnm	ASTM D5185m	mind bacc	0	0	0
Barium	ppm	ASTM D5185m	90	4	0	0
		ASTM D5185m	90	<1	0	0
Monganasa	ppm			<1 <1	0	0
Manganese	ppm	ASTM D5185m ASTM D5185m	90		4	1
Magnesium	ppm			6	0	0
Calcium	ppm	ASTM D5185m	2	3		
Phosphorus	ppm	ASTM D5185m		2	2	10
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		18325	14954	17801
CONTAMINANTS		method	limit/base		history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	<1
Sodium	ppm	ASTM D5185m		0	1	<1
Potassium	ppm	ASTM D5185m	>20	<1	0	<1
Water	%	ASTM D6304	>0.05	0.007	0.008	0.004
ppm Water	ppm	ASTM D6304	>500	76	85.4	47.3
FLUID CLEANLIN	IESS	method	limit/base		history1	history2
Particles >4μm		ASTM D7647		9741		895
Particles >6µm		ASTM D7647	>1300	<u>2308</u>		241
Particles >14μm		ASTM D7647	>80	<u> </u>		22
Particles >21μm		ASTM D7647		25		7
Particles >38μm		ASTM D7647	>4	0		0
Particles >71μm		ASTM D7647	>3	0		0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<b>20/18/14</b>		17/15/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.49	0.48	0.43



## **OIL ANALYSIS REPORT**







Certificate 12367

Laboratory Sample No.

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA012727 Lab Number : 06158470 Unique Number: 10993893

Received **Tested** Diagnosed

: 23 Apr 2024 : 25 Apr 2024

: 25 Apr 2024 - Angela Borella

Test Package : IND 2 ( Additional Tests: KF, PrtCount )

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

9005 SMITHS MILL RD NEW ALBANY, OH US 43054

**AXIUM PLASTICS** 

Contact: P. LONGIA plongia@axiumplastics.com

T: F: