


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL

Machine Id

VAC 1178633-3 NORTH (S/N U061401703)

Component **Pump**

USPI VAC 100 (--- GAL)

וח	$\Lambda C N$	JOS	ıc

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		eb2017 Oct201	7 Apr2018 Dec2018 Jul20	019 May2020 May2021 Feb2022 Ju	12023 Apr202	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USPM36808	USPM31312	USPM27378
Sample Date		Client Info		23 Apr 2024	18 Nov 2023	16 Jul 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	SEVERE
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>90	10	<1	4 05
Chromium	ppm	ASTM D5185m	>5	0	0	<1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	<1
Silver	ppm	ASTM D5185m	>3	0	0	0
Aluminum	ppm	ASTM D5185m	>7	0	0	▲ 13
Lead	ppm	ASTM D5185m	>12	0	0	0
Copper	ppm	ASTM D5185m	>30	0	0	<1
Tin	ppm	ASTM D5185m	>9	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	<1
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	0	<1	<1	3
Calcium	ppm	ASTM D5185m	0	<1	4	3
Phosphorus	ppm	ASTM D5185m	1800	1317	726	1203
Zinc	ppm	ASTM D5185m	0	0	0	0
Sulfur	ppm	ASTM D5185m	0	34	66	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>60	3	17	4
Sodium	ppm	ASTM D5185m		1	0	6
Potassium	ppm	ASTM D5185m	>20	0	0	2
Water	%	ASTM D6304	>.1	0.047	0.034	△ 0.130
ppm Water	ppm	ASTM D6304	>1000	470	348.6	▲ 1305.1
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	1244	8294	2428
Particles >6µm		ASTM D7647	>1300	260	▲ 5319	357
Particles >14μm		ASTM D7647	>160	41	<u>▲</u> 1602	9
Particles >21µm		ASTM D7647	>40	12	▲ 594	1
Particles >38μm		ASTM D7647	>10	3	<u>^</u> 27	0
Particles >71μm		ASTM D7647	>3	0	2	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	17/15/13	2 0/20/18	18/16/10
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
A sist Niverstans (ANI)	ma 1/011/-	ACTM DOGAE	0.05	0.00	0.14	A 7 470

0.28

mg KOH/g ASTM D8045 0.05

Acid Number (AN)

0.14

1.479



OIL ANALYSIS REPORT





Certificate 12367

Laboratory Sample No. Lab Number Unique Number : 10994558 Test Package : IND 2

: USPM36808 : 06159135

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 24 Apr 2024 **Tested** : 25 Apr 2024

Diagnosed

: 26 Apr 2024 - Jonathan Hester

JBS - BEARDSTOWN 8295 ARENZVILLE RD BEARDSTOWN, IL US 62618 Contact:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

 st - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) T:

F: