<u>Sullivan</u> Palatek

OIL ANALYSIS REPORT

Area **S9000 BOGE 5141493 - MORCON CONSTRUCTION**

Compressor

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend





NORMAL

| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
|------------------|---------------|-------------|------------|-------------|----------|----------|
| Sample Number | | Client Info | | UCS06159217 | | |
| Sample Date | | Client Info | | 09 Apr 2024 | | |
| Machine Age | hrs | Client Info | | 23537 | | |
| Oil Age | hrs | Client Info | | 4800 | | |
| Oil Changed | | Client Info | | Changed | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATIO | N | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | | |
| Chromium | ppm | ASTM D5185m | >10 | <1 | | |
| Nickel | ppm | ASTM D5185m | | <1 | | |
| Titanium | ppm | ASTM D5185m | | <1 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | 2 | | |
| Lead | ppm | ASTM D5185m | >25 | <1 | | |
| Copper | ppm | ASTM D5185m | >50 | <1 | | |
| Tin | ppm | ASTM D5185m | >15 | <1 | | |
| Vanadium | ppm | ASTM D5185m | | <1 | | |
| Cadmium | ppm | ASTM D5185m | | <1 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | <1 | | |
| Molybdenum | ppm | ASTM D5185m | | <1 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | | <1 | | |
| Calcium | ppm | ASTM D5185m | | 4 | | |
| Phosphorus | ppm | ASTM D5185m | | 70 | | |
| Zinc | ppm | ASTM D5185m | | 80 | | |
| Sulfur | ppm | ASTM D5185m | | 0 | | |
| CONTAMINANTS | \$ | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | <1 | | |
| Sodium | ppm | ASTM D5185m | | 5 | | |
| Potassium | ppm | ASTM D5185m | >20 | 1 | | |
| FLUID DEGRADA | ATION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D8045 | | 0.59 | | |



OIL ANALYSIS REPORT





| VISUAL | | method | limit/base | current | nistory i | nistoryz | | |
|---|---|-----------|--|---|------------|--|--|--|
| White Metal | scalar | *Visual | NONE | NONE | | | | |
| Yellow Metal | | *Visual | NONE | NONE | | | | |
| Precipitate | scalar | *Visual | NONE | NONE | | | | |
| Silt | scalar | *Visual | NONE | NONE | | | | |
| Debris | scalar | *Visual | NONE | NONE | | | | |
| Sand/Dirt | | *Visual | NONE | NONE | | | | |
| Appearance | scalar | *Visual | NORML | NORML | | | | |
| Odor | | *Visual | NORML | NORML | | | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | | | |
| Free Water | scalar | *Visual | | NEG | | | | |
| FLUID PROPER | | method | limit/base | current | history1 | history | | |
| | | | | | TIIStOry I | | | |
| /isc @ 40°C | cSt | ASTM D445 | Ď | 61.2 | | | | |
| SAMPLE IMAGE | S | method | limit/base | current | history1 | history2 | | |
| Color | | | | | no image | no image | | |
| Bottom | | | | | no image | no image | | |
| Non-ferrous Meta | ls | | Apr9/24 | | | | | |
| Viscosity @ 40°C | | | 9.0. | Acid Number | | | | |
| Abnormal (2-0+) 1/3 55 50 + + - - - - - - - - - - - - - | | | Apr8/24 4000 Apr8/24 Apr8/2 | 2 6 7 10 10 10 10 10 10 10 10 10 10 10 10 10 | | | | |
| | VearCheck USA - 501 Madison Ave., Cary, NC 27513 | | | | | | | |
| : UCS06159217 : 06159217 : 10994640 : IND 2 | S06159217 Received : 24 Apr 2024 159217 Tested : 25 Apr 2024 994640 Diagnosed : 26 Apr 2024 - Jonathan Hester | | | | | WEST FARGO, N US 580 Contact: DALE | | |

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Contact/Location: DALE K - UCJEMWES

dalek@jemco-maxair.com T: (701)281-0362

Page 2 of 2

F: x: