

OIL ANALYSIS REPORT

Area SMART OIL 6000 Machine Id HERTZ HVD0008 - GOLDEN ALTOS ROOF

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL

SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UHK06159228		
Sample Date		Client Info		10 Mar 2024		
Machine Age	hrs	Client Info		25351		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		11		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m	20	3		
Phosphorus	ppm	ASTM D5185m		301		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		274		
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.59		



OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current		history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Mar10/24	Appearance	scalar	*Visual	NORML	NORML		
Mar	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	54.0		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Mar10/24 +	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Meta	ls		Mart 0/24			
	0 Mar10/24			Mar10/24			
	Viscosity @ 40°C				Acid Number		
				(B)H0.48			
	() 50 0			Ĕ 0.36			
	() 50 () 50 () 50 () 50 () 50 () 50 () 50 () 50 () 50 () 50 () 50 () 50 () 50)			e 0.24			
	Abnormal			(0.60) (0.48) (0.36) (0.24) (0.12) (0.12) (0.12)			
	40			0.00	24		
	Mar1 0/24			Mar10/24	Mar10/24		
Laboratory Sample No.	: WearCheck USA - 50 : UHK06159228	1 Madisc Rece	ived : 24	, NC 27513 Apr 2024 Apr 2024	ETE ENGINEERED SOLUTIONS - Cl 772 FRONTIER WAY UNIT 40 STOCKTON, C US 952 Contact: CHRISTO GINGRA christo@complete-es.n		

* - Denotes test methods that Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: CHRISTO GINGRAS - UCCOMSTO

F: (209)753-4211