

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area SULLUBE [125890] SULLAIR 201203150002 - INNOMARK COMMUNICATIONS Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	/IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06159251		
Sample Date		Client Info		22 Apr 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	M	method	limit/base	current	history1	history2
Water	N		>0.1	NEG	Thistory	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	<1		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m	745	751		
Molybdenum	ppm	ASTM D5185m	0.0	<1		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	0.0	<1		
Calcium	ppm	ASTM D5185m	1	5		
Phosphorus	ppm	ASTM D5185m	3	8		
Zinc	ppm	ASTM D5185m	0.1	<1		
Sulfur	ppm	ASTM D5185m	240	200		
CONTAMINANTS	; 	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3		
Sodium	ppm	ASTM D5185m		11		
Potassium	ppm	ASTM D5185m	>20	1		
FLUID DEGRADA		method	limit/base	current	history1	history2
		ASTM D8045	.06	0.09		, in the second s
Acid Number (AN)	mg KOH/g	ASTIVI D8045	.00	0.09		



OIL ANALYSIS REPORT

VISUAL



	VISUAL						
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
		scalar	*Visual	NORML	NORML		
	Appearance Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar					
			*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	38.1	37.6		
	SAMPLE IMAGE	ES	method	limit/base	current	history1	history2
	Color					no image	no image
	Bottom					no image	no image
	Ferrous Alloys						
	10 8 6 4 2 - - - - - - - - - - - - -	als		Apr22/24	Acid Number		
	Non-ferrous Meta	als		Apr22/24	Acid Number		
	Non-ferrous Meta	als		Apr22/24	Acid Number		
	Non-ferrous Meta und 0 0 0 0 0 0 0 0 0 0 0 0 0	als		Apr22/24	Acid Number		
	Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C	als		Apr22/24	Acid Number		
	Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C	als		Apr22224 Apr22224 Apr22224 Apr22224 Apr22224	Severe Abnormal Base		
	Non-ferrous Meta Non-ferrous Meta Viscosity @ 40°C	als		Apr22224 Apr22224 Apr22224 Apr22224 Apr22224	Severe Abnormal Base		
XXCC 17025	y : WearCheck USA - 50 0. : UCH06159251 ber : 06159251	als 01 Madisc Recei Teste	on Ave., Cary ived : 24	**************************************	Severe Abnormal Base H0220dW	203	ENGINEERIN D SHIPLEY D ALISBURY, M US 218(
Sample N Lab Numb Unique Num	Viscosity @ 40°C	als 01 Madisc Recei Teste	on Ave., Cary ived : 24	+272704 +272704 +272704 (0)HQ, 2.00 00HQ, 2.00 00	Severe Abnormal Base H0220dW	203	ENGINEERIN D SHIPLEY D ALISBURY, M US 2180

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Page 2 of 2