

## **OIL ANALYSIS REPORT**

Sample Rating Trend





Machine Id VOLVO A30G 340072

Component Bogie/Center Axle

# GEAR OIL SAE 80W140 (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.


### Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method				history2
Sample Number		Client Info		ML0000984		
Sample Date		Client Info		22 Apr 2024		
Machine Age	hrs	Client Info		11356		
Oil Age	hrs	Client Info		11356		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATION	J	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>900	29		
Chromium	ppm	ASTM D5185m	>20	0		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>30	0		
Lead	ppm	ASTM D5185m	>50	0		
Copper	ppm	ASTM D5185m		3		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium		ASTM D5185m	>20	0		
Cadmium	ppm			-		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	400	111		
Barium	ppm	ASTM D5185m	200	0		
Molybdenum	ppm	ASTM D5185m	12	0		
Vanganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m	12	16		
Calcium	ppm	ASTM D5185m	150	136		
Phosphorus	ppm	ASTM D5185m	1650	970		
Zinc	ppm	ASTM D5185m	125	66		
Sulfur	ppm	ASTM D5185m	22500	30405		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	4		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	0		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
28:50) Rev: 1	Julia	Visual			itted By: Service	



## **OIL ANALYSIS REPORT**



FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	263	285		
SAMPLE IMAC	GES	method	limit/base	current	history1	history2
Color				no image	no image	no image
47/77/dH						<u></u>
Bottom				no image	no image	no image
GRAPHS						
Ferrous Alloys						
25 - iron iron chromium						
20 -						
틆 15 -						
10						
5-						
0						
Apr22/24			Apr22/24			
⊲ Non-ferrous Me	etals		Ä			
9 copper						
8 - ensemble lead						
6						
Ē. 5						
3 -						
2						
24 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			/24			
Apr22/24			Apr22/24			
Viscosity @ 40 <sup>4</sup>	°C					
300 -						
280						
유 (유) (유) (유) (유) (유) (유) (유) (유) (유) (유						
240 -						
Abnormal						
200			2/24			
Apr22/24			Apr22/24			
y :WearCheck USA - b. :ML0000984 er :06159488 per :10994911 ge :CONST	Reco Test	eived : 24 red : 25	, NC 27513 Apr 2024 Apr 2024 Apr 2024 - Jona	than Hester		ILLIAM HAZ PO BOX 6 HANTILLY, ' US 201



US 20153 Contact: SERVICE MANAGER jimmy\_elswick@wahazel.com T: (703)378-8300 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F:

Report Id: WILCHA [WUSCAR] 06159488 (Generated: 04/26/2024 11:28:50) Rev: 1

Certificate 12367

Test Package : CONST

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Submitted By: Service - William Brittle

Page 2 of 2