


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

KAESER ESD 300 6243068 (S/N 1482)

Component Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil. Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Apr2021 Mar2022 Jun20	22 Aug2022 Nov2022 May2023	Apr2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA012718	KCP53986	KCP52132
Sample Date		Client Info		19 Apr 2024	23 May 2023	21 Nov 2022
Machine Age	hrs	Client Info		44787	36926	32627
Oil Age	hrs	Client Info		0	4299	2200
Oil Changed		Client Info		Changed	Changed	Not Changd
Sample Status				ABNORMAL	ABNORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	2	0
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	1	0	<1
Titanium	ppm	ASTM D5185m	>3	<1	<1	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>10	2	<1	0
Lead	ppm	ASTM D5185m	>10	1	0	<1
Copper	ppm	ASTM D5185m	>50	6	0	6
Tin	ppm	ASTM D5185m	>10	1	4	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	<1	0	0
Molybdenum	ppm	ASTM D5185m		1	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	90	13	0	<1
Calcium	ppm	ASTM D5185m	2	3	0	0
Phosphorus	ppm	ASTM D5185m		2	10	10
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		19226	17	18696
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	7	1
Sodium	ppm	ASTM D5185m		0	0	<1
Potassium	ppm	ASTM D5185m	>20	2	0	<1
Water	%	ASTM D6304	>0.05	0.018	0.003	0.006
ppm Water	ppm	ASTM D6304	>500	182	27.8	69.1
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		36563	132090	6709
Particles >6µm		ASTM D7647	>1300	<u> </u>	▲ 48977	2126
Particles >14μm		ASTM D7647	>80	<u> </u>	<u>^</u> 2133	96
Particles >21µm		ASTM D7647	>20	<u> </u>	<u>454</u>	36
Particles >38μm		ASTM D7647	>4	<u> </u>	<u>12</u>	5
Particles >71µm		ASTM D7647	>3	1	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>22/21/17</u>	<u>4</u> 24/23/18	20/18/14
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.47	0.49	0.44



OIL ANALYSIS REPORT







Laboratory Sample No.

Lab Number Unique Number: 10995221

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA012718 : 06159798

Received : 24 Apr 2024 **Tested** Diagnosed

: 25 Apr 2024

: 26 Apr 2024 - Don Baldridge Test Package : IND 2 (Additional Tests: KF, PrtCount)

Certificate 12367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

plongia@axiumplastics.com

US 43054

T:

F:

AXIUM PLASTICS

NEW ALBANY, OH

Contact: P. LONGIA

9005 SMITHS MILL RD