

OIL ANALYSIS REPORT

OKLAHOMA/115/EG - LOADER 48.83L [OKLAHOMA^115^EG - LOADER]

Sample Rating Trend




NORMAL


Diesel Engine MOBIL DELVAC 1300 SUPER15W40 (--- GAL)


AGNOSIS	SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
ommendation	Sample Number		Client Info		WC0848872	WC0886934	WC0778379
ample at the next service interval to monitor.	Sample Date		Client Info		05 Apr 2024	24 Jan 2024	24 Aug 2023
ar	Machine Age	hrs	Client Info		11425	11071	10809
component wear rates are normal.	Oil Age	hrs	Client Info		260	250	19800
tamination	Oil Changed		Client Info		Changed	Changed	Changed
re is no indication of any contamination in the	Sample Status				NORMAL	NORMAL	NORMAL
pil.	CONTAMINATIO	N	method	limit/base	current	history1	history2
Fluid Condition The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.	Fuel		WC Method	>5	<1.0	<1.0	<1.0
	Water		WC Method	>0.2	NEG	NEG	NEG
	Glycol		WC Method	,	NEG	NEG	NEG
	WEAR METALS		method	limit/base		history1	history2
	Iron	ppm	ASTM D5185m		7	10	23
	Chromium		ASTM D5185m		0	0	<1
	Nickel	ppm	ASTM D5185m		0	<1	< 1
		ppm					
	Titanium Silver	ppm	ASTM D5185m		0	0	0
		ppm	ASTM D5185m		0	0	0
	Aluminum	ppm	ASTM D5185m		<1	2	2
	Lead	ppm	ASTM D5185m		0	0	0
	Copper	ppm	ASTM D5185m		2	2	5
	Tin	ppm	ASTM D5185m	>4	0	<1	<1
	Vanadium	ppm	ASTM D5185m		0	0	0
	Cadmium	ppm	ASTM D5185m		0	0	0
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185m	0	56	56	44
	Barium	ppm	ASTM D5185m	0	0	0	0
	Molybdenum	ppm	ASTM D5185m	0	41	39	40
	Manganese	ppm	ASTM D5185m		0	<1	<1
	Magnesium	ppm	ASTM D5185m	0	541	497	510
	Calcium	ppm	ASTM D5185m		1815	1615	1661
	Phosphorus	ppm	ASTM D5185m		808	782	735
	Zinc	ppm	ASTM D5185m		949	890	880
	Sulfur	ppm	ASTM D5185m		3046	2512	2879
	CONTAMINANTS		method	limit/base	current	history1	history2
	Silicon	ppm	ASTM D5185m	>20	4	7	4
	Sodium	ppm	ASTM D5185m		2	3	3
	Potassium	ppm	ASTM D5185m	>20	0	2	<1
	INFRA-RED		method	limit/base	current	history1	history2
	Soot %	%	*ASTM D7844	>3	0.3	0.4	0.8
	Nitration	Abs/cm	*ASTM D7624	>20	6.7	6.4	7.1
	Sulfation	Abs/.1mm	*ASTM D7415	>30	21.8	22.1	22.4
	FLUID DEGRADA	TION	method	limit/base	current	history1	history2
	Oxidation	Abs/.1mm	*ASTM D7414	>25	19.7	19.5	19.5



OIL ANALYSIS REPORT










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	TIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14	12.6	12.7	12.7
СРАРИС						

Ferrous Alloys







Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513 SHERWOOD CONSTRUCTION CO INC : WC0848872 Sample No. Received : 25 Apr 2024 3219 WEST MAY ST Lab Number : 06160080 Tested : 25 Apr 2024 WICHITA, KS Unique Number : 10995503 Diagnosed : 25 Apr 2024 - Wes Davis US 67213 Test Package : CONST (Additional Tests: TBN) Contact: DOUG KING Certificate 12367 doug.king@sherwood.net To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. T: (316)617-3161 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: x:

Submitted By: PATRICIA BIBLE

Page 2 of 2