




OIL ANALYSIS REPORT

Area
OKLAHOMA/3/EG - TRUCK-OFF-HWY-HEAVY HAUL
 Machine Id
69.03 [OKLAHOMA^3^EG - TRUCK-OFF-HWY-HEAVY HAUL]
 Component
Diesel Engine
 Fluid
MOBIL 15W40 (--- GAL)

Sample Rating Trend



NORMAL



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0914454	WC0874010	WC0874028
Sample Date	Client Info		17 Apr 2024	31 Jan 2024	15 Dec 2023
Machine Age	hrs	Client Info	1943	1448	1050
Oil Age	hrs	Client Info	1448	1050	1050
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	MARGINAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	11	8	15
Chromium	ppm	ASTM D5185m >20	<1	<1	<1
Nickel	ppm	ASTM D5185m >2	0	<1	0
Titanium	ppm	ASTM D5185m >2	0	0	<1
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >25	2	2	3
Lead	ppm	ASTM D5185m >40	0	<1	<1
Copper	ppm	ASTM D5185m >330	1	2	8
Tin	ppm	ASTM D5185m >15	0	<1	<1
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	49	49	50
Barium	ppm	ASTM D5185m	0	0	0
Molybdenum	ppm	ASTM D5185m	42	36	41
Manganese	ppm	ASTM D5185m	0	<1	<1
Magnesium	ppm	ASTM D5185m	537	467	500
Calcium	ppm	ASTM D5185m	1847	1539	1648
Phosphorus	ppm	ASTM D5185m	801	711	731
Zinc	ppm	ASTM D5185m	959	839	910
Sulfur	ppm	ASTM D5185m	3209	2315	2708

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	4	6	13
Sodium	ppm	ASTM D5185m >118	3	4	0
Potassium	ppm	ASTM D5185m >20	0	<1	1
Fuel	%	ASTM D3524 >5	<1.0	<1.0	▲ 2.6

INFRA-RED





	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.2	0.2	0.2
Nitration	Abs/cm	*ASTM D7624 >20	6.6	6.4	6.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.4	21.5	21.8

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	19.7	19.6	20.0
Base Number (BN)	mg KOH/g	ASTM D2896	9.4	10.1	9.9







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.3	12.0	11.9

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0914454 **Received** : 25 Apr 2024
Lab Number : 06160087 **Tested** : 26 Apr 2024
Unique Number : 10995510 **Diagnosed** : 26 Apr 2024 - Sean Felton
Test Package : CONST (Additional Tests: FuelDilution, TBN)

SHERWOOD CONSTRUCTION CO INC
 3219 WEST MAY ST
 WICHITA, KS
 US 67213
 Contact: SHAWN SOUTH
 shawn.south@sherwood.net

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: x:
F: x: