




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
614
 Component
Diesel Engine
 Fluid
{not provided} (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			AK0000014	AK0000012	AK0000032
Sample Date	Client Info			17 Apr 2024	27 Mar 2024	05 Mar 2024
Machine Age	mls	Client Info		665179	656160	646014
Oil Age	mls	Client Info		51100	42081	31935
Oil Changed	Client Info			Not Changed	Not Changed	Not Changed
Sample Status				NORMAL	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Water	WC Method		>0.2	NEG	NEG	NEG
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>90	103	77	66
Chromium	ppm	ASTM D5185m	>20	6	4	4
Nickel	ppm	ASTM D5185m	>2	1	0	0
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	<1
Aluminum	ppm	ASTM D5185m	>20	4	3	3
Lead	ppm	ASTM D5185m	>40	4	1	1
Copper	ppm	ASTM D5185m	>330	2	<1	0
Tin	ppm	ASTM D5185m	>15	2	<1	<1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0





ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	1	<1
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		65	61	59
Manganese	ppm	ASTM D5185m		2	1	1
Magnesium	ppm	ASTM D5185m		992	961	960
Calcium	ppm	ASTM D5185m		1129	1073	1024
Phosphorus	ppm	ASTM D5185m		1020	1037	1050
Zinc	ppm	ASTM D5185m		1282	1255	1259
Sulfur	ppm	ASTM D5185m		2887	3063	2719

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	6	4	4
Sodium	ppm	ASTM D5185m		0	<1	1
Potassium	ppm	ASTM D5185m	>20	4	<1	2
Fuel	%	ASTM D3524	>3.0	<1.0	<1.0	<1.0

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>6	0.5	0.4	0.3
Nitration	Abs/cm	*ASTM D7624	>20	11.6	10.4	9.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	30.5	29.0	27.2

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	29.0	26.9	24.5
Base Number (BN)	mg KOH/g	ASTM D2896		4.3	5.1	8.14









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	8.9	8.8	8.4

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : AK0000014
Lab Number : 06160206
Unique Number : 10995629
Test Package : MOB 1 (Additional Tests: FuelDilution, TBN)
Received : 25 Apr 2024
Tested : 26 Apr 2024
Diagnosed : 26 Apr 2024 - Don Baldrige

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

MEYER LOGISTICS
 560 EAST 25TH ST
 JASPER, IN
 US 47546
 Contact: KEN FROMME
 kenny.fromme@meyerdistributing.com
 T: (812)639-9224
 F: