

OIL ANALYSIS REPORT

Area DF8 PLUS KAESER 4207926 - VEEPAK (S/N 1024) Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.




Sample Rating Trend



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UDI0000120		
Sample Date		Client Info		12 Apr 2024		
Machine Age	hrs	Client Info		109289		
Oil Age	hrs	Client Info		18649		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.05	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>3	<1		
Titanium	ppm	ASTM D5185m	>3	<1		
Silver	ppm	ASTM D5185m	>2	0		
Aluminum	ppm	ASTM D5185m	>10	2		
Lead	ppm	ASTM D5185m	>10	<1		
Copper	ppm	ASTM D5185m	>50	1		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1	0		
Barium	ppm	ASTM D5185m	0.3	0		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m	0	<1		
Magnesium	ppm	ASTM D5185m	0	<1		
Calcium	ppm	ASTM D5185m	0.5	0		
Phosphorus	ppm	ASTM D5185m	536	23		
Zinc	ppm	ASTM D5185m	0.2	13		
Sulfur	ppm	ASTM D5185m	649	1174		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	19		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.337	0.27		



OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Apr12/24	Appearance	scalar	*Visual	NORML	NORML		
Ap	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.05	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	42.0	47.3		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Apr12/24	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Meta			Apr12/24			
	Apr12/24			Apr12/24			
	, but			Apri			
	Viscosity @ 40°C			,-	Acid Number		
				(B) 0.4	Acid Number		
	Viscosity @ 40°C			(B/HOX 0.3 Bu	Acid Number		
	Viscosity @ 40°C			0.4 (D) HOX WO W U Q U Q U Q U Q U Q U Q U Q U Q U Q U	Acid Number		
	Viscosity @ 40°C			0.4 (5)HO W KON Bu Ja Q W M V M W U 0.1	Acid Number		
	Viscosity @ 40°C			6.0 (0) (0) (0) (0) (0) (0) (0) (0) (0) (0	Base		
	Viscosity @ 40°C				Base		
Laboratory	Viscosity @ 40°C			Apr12/24	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	IDUSTRIES - DO	

Report Id: UCDELDOW [WUSCAR] 06160537 (Generated: 04/26/2024 15:30:23) Rev: 1

Contact/Location: MICHAEL FERRIS - UCDELDOW

Page 2 of 2