


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



RO NFDM [1958704] RO02PP21BB01

Bearing

MOBIL SHC 626 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The water content is negligible. There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

		,	AFOED OUTDED THIEDET	ONLOSE PRINCES ONLOSE ONLO	LO TOPICOLI	
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0927365	WC0864100	WC0747528
Sample Date		Client Info		18 Apr 2024	18 Oct 2023	17 Oct 2022
Machine Age	mths	Client Info		0	0	0
Oil Age	mths	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	SEVERE	ABNORMAL
CONTAMINATION	١	method	limit/base	current	history1	history2
Water		WC Method	>2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	1	4	1
Chromium	ppm	ASTM D5185m	>20	0	0	0
Nickel	ppm	ASTM D5185m	>20	0	0	0
Titanium	ppm	ASTM D5185m	-	<1	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	0	<1	<1
Lead	ppm	ASTM D5185m	>20	<1	1	<1
Copper	ppm	ASTM D5185m	>20	2	5	2
Tin	ppm	ASTM D5185m	>20	0	<1	<1
Vanadium	ppm	ASTM D5185m	720	0	0	0
Cadmium		ASTM D5185m		0	0	0
	ppm		12 14 17	-		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		<1	10	<1
Calcium	ppm	ASTM D5185m		8	9	15
Phosphorus	ppm	ASTM D5185m		462	435	435
Zinc	ppm	ASTM D5185m		14	18	32
Sulfur	ppm	ASTM D5185m		1163	867	1207
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	1	3	<1
Sodium	ppm	ASTM D5185m		0	0	<1
Potassium	ppm	ASTM D5185m	>20	<1	<1	<1
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	▲ MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>2	NEG	0.2%	NEG
Free Water	scalar	*Visual	-	NEG	▲ >10%	NEG
1.48.22\ Rov. 1	Journal	Vioudi			ad By: MICHAE	



OIL ANALYSIS REPORT





GRAPHS Ferrous Alloys Non-ferrous Metals Viscosity @ 40°C 74 72 62



Certificate 12367

Laboratory Test Package : IND 1

Sample No. : WC0927365 Lab Number : 06160856 Unique Number : 10996279

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received **Tested** Diagnosed

: 25 Apr 2024 : 26 Apr 2024

: 29 Apr 2024 - Don Baldridge

LEPRINO FOODS-GREELEY 1302 1ST AVE GREELEY, CO US 80631-5909

Contact: ERIC KLINE EKLINE@LEPRINOFOODS.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

F: (970)347-5190 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)