


# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machine Id

# 5942314 (S/N 2010)

Component Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

## **DIAGNOSIS**

#### Recommendation

No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is a high amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		0ct202	1 May2023	NovŽ023 Ap	r2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA012501	KCPA011385	KCPA001949
Sample Date		Client Info		20 Apr 2024	15 Nov 2023	24 May 2023
Machine Age	hrs	Client Info		36703	32939	29240
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	N/A	N/A
Sample Status				ABNORMAL	NORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	<1	0
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	0	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	5	8	6
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	100	0	<1	0
Calcium	ppm	ASTM D5185m	0	0	1	0
Phosphorus	ppm	ASTM D5185m	0	4	<1	0
Zinc	ppm	ASTM D5185m	0	1	0	0
Sulfur	ppm	ASTM D5185m	23500	21736	17423	17733
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	1	<1
Sodium	ppm	ASTM D5185m		2	<1	<1
Potassium	ppm	ASTM D5185m	>20	3	1	0
Water	%	ASTM D6304		0.004	0.003	0.006
ppm Water	ppm	ASTM D6304	>500	44	31	65.6
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		14116	535	979
Particles >6µm		ASTM D7647	>1300	<b>4347</b>	133	466
Particles >14μm		ASTM D7647	>80	<b>410</b>	10	138
Particles >21µm		ASTM D7647	>20	<u> </u>	3	<b>48</b>
Particles >38µm		ASTM D7647	>4	<u>^</u> 6	0	3
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>21/19/16</u>	16/14/10	17/16/14
FLUID DEGRADA	TION	method	limit/base	current	history1	history2



## OIL ANALYSIS REPORT







Certificate 12367

Sample No.

Laboratory

Lab Number

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : KCPA012501 : 06160942

Unique Number : 10996365

Received : 25 Apr 2024 **Tested** 

: 26 Apr 2024 Diagnosed

: 29 Apr 2024 - Don Baldridge Test Package : IND 2 ( Additional Tests: KF, PrtCount )

To discuss this sample report, contact Customer Service at 1-800-237-1369.  $^st$  - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**PROMEX INDUSTRIES INC** 

3075 OAKMEAD VILLAGE DR SANTA CLARA, CA US 95051

Contact/Location: W. LAM - PROSANCAL

Contact: W. LAM wlam@promex-ind.com

T: F: