



# OIL ANALYSIS REPORT

Sample Rating Trend



ISO



Machine Id

**8304726 (S/N 4292)**

Component

**Compressor**

Fluid

**KAESER SIGMA (OEM) M-460 (--- GAL)**

## DIAGNOSIS

### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is a high amount of particulates present in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>KCPA016423</b>	---	---
Sample Date	Client Info	<b>22 Apr 2024</b>	---	---
Machine Age	hrs	<b>2345</b>	---	---
Oil Age	hrs	<b>0</b>	---	---
Oil Changed	Client Info	<b>Not Changed</b>	---	---
Sample Status		<b>ABNORMAL</b>	---	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron ppm	ASTM D5185m >50	<b>&lt;1</b>	---	---
Chromium ppm	ASTM D5185m >10	<b>0</b>	---	---
Nickel ppm	ASTM D5185m >3	<b>0</b>	---	---
Titanium ppm	ASTM D5185m >3	<b>0</b>	---	---
Silver ppm	ASTM D5185m >2	<b>0</b>	---	---
Aluminum ppm	ASTM D5185m >10	<b>&lt;1</b>	---	---
Lead ppm	ASTM D5185m >10	<b>0</b>	---	---
Copper ppm	ASTM D5185m >50	<b>2</b>	---	---
Tin ppm	ASTM D5185m >10	<b>&lt;1</b>	---	---
Vanadium ppm	ASTM D5185m	<b>0</b>	---	---
Cadmium ppm	ASTM D5185m	<b>0</b>	---	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron ppm	ASTM D5185m 0	<b>0</b>	---	---
Barium ppm	ASTM D5185m 90	<b>16</b>	---	---
Molybdenum ppm	ASTM D5185m 0	<b>0</b>	---	---
Manganese ppm	ASTM D5185m	<b>&lt;1</b>	---	---
Magnesium ppm	ASTM D5185m 100	<b>48</b>	---	---
Calcium ppm	ASTM D5185m 0	<b>&lt;1</b>	---	---
Phosphorus ppm	ASTM D5185m 0	<b>1</b>	---	---
Zinc ppm	ASTM D5185m 0	<b>5</b>	---	---
Sulfur ppm	ASTM D5185m 23500	<b>22700</b>	---	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm	ASTM D5185m >25	<b>&lt;1</b>	---	---
Sodium ppm	ASTM D5185m	<b>10</b>	---	---
Potassium ppm	ASTM D5185m >20	<b>13</b>	---	---
Water %	ASTM D6304 >0.05	<b>0.029</b>	---	---
ppm Water	ASTM D6304 >500	<b>299</b>	---	---






## FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647	<b>27413</b>	---	---
Particles >6µm	ASTM D7647 >1300	<b>▲ 4642</b>	---	---
Particles >14µm	ASTM D7647 >80	<b>▲ 171</b>	---	---
Particles >21µm	ASTM D7647 >20	<b>▲ 31</b>	---	---
Particles >38µm	ASTM D7647 >4	<b>1</b>	---	---
Particles >71µm	ASTM D7647 >3	<b>0</b>	---	---
Oil Cleanliness	ISO 4406 (c) >--/17/13	<b>▲ 22/19/15</b>	---	---

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN) mg KOH/g	ASTM D8045 1.0	<b>0.40</b>	---	---


# OIL ANALYSIS REPORT







VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.05	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	45	43.9	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : KCPA016423 **Received** : 25 Apr 2024  
**Lab Number** : 06160945 **Tested** : 26 Apr 2024  
**Unique Number** : 10996368 **Diagnosed** : 29 Apr 2024 - Don Baldrige  
**Test Package** : IND 2 ( Additional Tests: KF, PrtCount )

**CT NASSAU TICKING LLC**  
 1504 ANTHONY RD  
 BURLINGTON, NC  
 US 27215  
 Contact: BRIAN ROBERTS  
 brian.g.roberts.82@gmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)