


OIL ANALYSIS REPORT



EDLTAY TAYM03BE (S/N 1256582) Component Biogas Engine

CHEVRON HDAX 9500 GAS ENGINE OIL 40 (180 GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	IATION	method	limit/base			history2
Sample Number		Client Info		WC0901633	WC0901607	WC0901601
Sample Date		Client Info		25 Apr 2024	10 Apr 2024	03 Apr 2024
Machine Age	hrs	Client Info		55664	55664	55664
Oil Age	hrs	Client Info		144	545	377
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	SEVERE	NORMAL
CONTAMINATION	۱	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Water		WC Method		NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>14	2	2	0
Chromium	ppm	ASTM D5185m	>3	<1	<1	0
Nickel	ppm	ASTM D5185m		0	<1	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm		>5	2	3	2
Lead	ppm	ASTM D5185m	>6	0	2	0
Copper	ppm	ASTM D5185m	>5	<1	<1	0
Tin	ppm	ASTM D5185m	>6	<1	5	3
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		2	3	2
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		5	7	7
Calcium	ppm	ASTM D5185m		1913	2039	1864
Phosphorus	1-1-					
	mag	ASTM D5185m				
· · · · · · · · · · · · · · · · · · ·	ppm	ASTM D5185m		260	289	257
Zinc	ppm ppm					
Zinc	ppm	ASTM D5185m	limit/base	260 313	289 356	257 326 3380
Zinc Sulfur CONTAMINANTS	ppm	ASTM D5185m ASTM D5185m	limit/base >180	260 313 3284	289 356 4142	257 326 3380
Zinc Sulfur CONTAMINANTS Silicon	ppm	ASTM D5185m ASTM D5185m method		260 313 3284 current	289 356 4142 history1	257 326 3380 history2
Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m	>180	260 313 3284 current	289 356 4142 history1	257 326 3380 history2
Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m	>180	260 313 3284 current 6 3	289 356 4142 history1 13	257 326 3380 history2 9 5 4
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	>180 >20	260 313 3284 current 6 3	289 356 4142 history1 13 4 7	257 326 3380 history2 9 5
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m method	>180 >20 limit/base >2	260 313 3284 current 6 3 2	289 356 4142 history1 13 4 7 history1	257 326 3380 history2 9 5 4 history2
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844	>180 >20 limit/base >2 >2 >20	260 313 3284 current 6 3 2 current 0	289 356 4142 history1 13 4 7 history1	257 326 3380 history2 9 5 4 history2
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm Abs/cm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624	>180 >20 limit/base >2 >2 >20	260 313 3284	289 356 4142 history1 13 4 7 history1 0 5.3	257 326 3380 history2 9 5 4 history2 0 5.1 22.5
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm Abs/cm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624 *ASTM D7415	>180 >20 limit/base >2 >2 >20 >30	260 313 3284 current 6 3 2 current 0 5.0 20.1	289 356 4142 history1 13 4 7 history1 0 5.3 23.3	257 326 3380 history2 9 5 4 history2 0 5.1
Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm ppm ppm ppm Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D7624 *ASTM D7624 *ASTM D7415 method	>180 >20 limit/base >2 >20 >30 limit/base	260 313 3284	289 356 4142 history1 13 4 7 history1 0 5.3 23.3 history1	257 326 3380 history2 9 5 4 history2 0 5.1 22.5




OIL ANALYSIS REPORT












VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual		NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPER	HES	method	limit/base		nistory1	history2
Visc @ 100°C	cSt	ASTM D445	13.4	13.1	13.4	13.3


Seve	re		7777				
100	ormal						
5	/	1	\ .	1			
	1	1	~	1	_ ^	1	~
	- V	-			7		
Aug30/19	0ct22/19 -	Jan6/20	Jan 15/21	Aug1/23	Nov16/23	Jan23/24	Mar5/24





















Certificate 12367

Laboratory Sample No.

Test Package : MOB 2

: WC0901633 Lab Number : 06161685 Unique Number : 10997108

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received

: 26 Apr 2024 **Tested** : 29 Apr 2024 Diagnosed : 29 Apr 2024 - Sean Felton **EDL NA Recips-Taylor County**

TAYLOR COUNTY POWER STATION, COUNTY ROAD 33 & STEWART ROAD MAUK, GA US 31058

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Contact: STEVEN BABB steven.babb@edlenergy.com T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: