

OIL ANALYSIS REPORT

ACS-46-5 [419839] ATLAS COPCO ITJ271790 - ROSE BRANDS

Component Compressor

Recommendation

Resample at the next service interval to monitor.

Wear

Area


All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL

SAMPLE INFORM	NATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06173954		
Sample Date		Client Info		17 Apr 2024		
Machine Age	hrs	Client Info		1776		
Oil Age	hrs	Client Info		256		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1		
Chromium	ppm	ASTM D5185m	>5	<1		
Nickel	ppm	ASTM D5185m		1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>15	<1		
Lead	ppm	ASTM D5185m	>65	<1		
Copper	ppm	ASTM D5185m	>65	1		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0.0	0		
Barium	ppm	ASTM D5185m	0.0	0		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m	0	<1		
Magnesium	ppm	ASTM D5185m	0.0	1		
Calcium	ppm	ASTM D5185m	0.0	0		
Phosphorus	ppm	ASTM D5185m	966	47		
Zinc	ppm	ASTM D5185m	0	122		
Sulfur	ppm	ASTM D5185m	1309	109		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	2		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	2		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.172	0.10		



OIL ANALYSIS REPORT

VISUAL



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Apr17/24	Appearance	scalar	*Visual	NORML	NORML		
Apr	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	39.9	47.7		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Apr17/24 +	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Meta	ls		Apr17/24	Acid Number		
	45 45 45 45 45 45 45 45 45 45 45 45 45 4			40117/24 Apri17/24 Apri17/24	1		
Laboratory Sample No. Lab Number Unique Number Test Package iscuss this sample report, enotes test methods that	: WearCheck USA - 50 : UCH06173954 : 06173954 : 11020007 : IND 2 , contact Customer Serv	Rece Teste Diagi	ived : 09 ed : 10 nosed : 12	r, NC 27513 9 May 2024 9 May 2024 May 2024 - Doi	AIRMAT n Baldridge	CA	GOR SYSTEM HINGTON AV RLSTADT, N US 0707 ct: ELVIN DIA

Report Id: UCAIRCAR [WUSCAR] 06173954 (Generated: 05/12/2024 09:29:30) Rev: 1

Contact/Location: ELVIN DIAZ - UCAIRCAR