

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area **ROTO XTEND [417592]** Machine to **ATLAS COPCO API270152 - SODEXO** Component

Component Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06173960		
Sample Date		Client Info		08 May 2024		
Machine Age	hrs	Client Info		21495		
Oil Age	hrs	Client Info		7122		
Oil Changed	1110	Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1		
Chromium	ppm	ASTM D5185m	>5	<1		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>15	<1		
Lead	ppm	ASTM D5185m	>65	<1		
Copper	ppm	ASTM D5185m	>65	2		
Tin	ppm	ASTM D5185m	>10	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		31		
Zinc	ppm	ASTM D5185m		56		
Sulfur	ppm	ASTM D5185m		61		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	2		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	2		
FLUID DEGRADA	TION_	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.14	0.27		
				0.2.		



May8/24

OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	NONE		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
May8/24	Appearance	scalar	*Visual	NORML	NORML		
2	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	46	48.9		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
May8/24	Color					no image	no image
	Bottom					no image	no image
	Non-ferrous Meta			May6/24			
	Viscosity @ 40°C			428/m 450.23	Acid Number		
	40 40 40 40 40 40 40 40 40 40 40 40 40 4			(b) 10.0 (b) HOX DEU HOX DEU H	Base +72/8/ke W		
Laboratory Sample No. Lab Number Unique Number	: WearCheck USA - 50 : UCH06173960 : 06173960	01 Madisc Rece Teste Diagr		IRMATIC COMPRESSOR SYSTEM 700 WASHINGTON AV CARLSTADT, N US 0707 Contact: ELVIN DIA az@airmaticcompressor.com;canastasio@wearcheckusa.c			

* - Denotes test methods that Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ELVIN DIAZ - UCAIRCAR

F: (201)342-6241