

## **OIL ANALYSIS REPORT**

### Area **ROTO XTEND [418927] ATLAS COPCO APF754189 - BERGEN GENERATING**

Component Compressor

#### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





Sample Rating Trend

SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06173972	UCH06141395	
Sample Date		Client Info		23 Apr 2024	07 Apr 2024	
Machine Age	hrs	Client Info		5814	5188	
Oil Age	hrs	Client Info		1800	0	
Oil Changed		Client Info		Not Changd	N/A	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	
Chromium	ppm	ASTM D5185m	>5	<1	0	
Nickel	ppm	ASTM D5185m		<1	0	
Titanium	ppm	ASTM D5185m		<1	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>15	5	8	
Lead	ppm	ASTM D5185m	>65	<1	0	
Copper	ppm	ASTM D5185m	>65	<1	0	
Tin	ppm	ASTM D5185m	>10	<1	0	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		<1	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		1	0	
Molybdenum	ppm	ASTM D5185m		<1	0	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m		<1	0	
Calcium	ppm	ASTM D5185m		0	0	
Phosphorus	ppm	ASTM D5185m		52	39	
Zinc	ppm	ASTM D5185m		65	74	
Sulfur	ppm	ASTM D5185m		30	61	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	1	<1	
Sodium	ppm	ASTM D5185m		<1	5	
Potassium	ppm	ASTM D5185m	>20	5	3	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.14	0.19	0.20	



# **OIL ANALYSIS REPORT**





VISUAL		methoa	iimii/base	current	nistory i	nistoryz
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	48.1	47.7	
SAMPLE IMAGES	3	method	limit/base	current	history1	history2
Color						no image
Bottom				$\bigcirc$		no image
GRAPHS						
8 iron 6 iron 6 iron 1 iron			Apr23/24			
Non-ferrous Metals	5		Apr23/24 +			
Viscosity @ 40°C				Acid Numbe	r	
Abnormal			<sup>©0.25</sup>	T		
50			(B) 0.25 (B) 0.20 (B) 0.20 (B) 0.15 (B) 0.15 (B) 0.15 (C) 0.05 (C) 0.05 (C) 0.05 (C) 0.05 (C) 0.25 (C)			
50 45			<u>ا</u> ق	Base		
			-	-		
Abnormal			- 0.05 9			
40 4						24
Apr7/24			Apr23/24	Apr7/24		Apr23/24
WearCheck USA - 50 <sup>-</sup> UCH06173972 06173972 11020025 IND 2 outoot Customer Service	Recei Teste Diagr	ived : 09 id : 10 nosed : 12	9 May 2024 9 May 2024 May 2024 - Don	Baldridge	CAI Contact	INGTON AVE RLSTADT, NJ US 07072 :: ELVIN DIAZ
ontact Customer Servi	ce at 1-8	00-237-1369	Э.	ediaz@ai	rmaticcompressor.com;canastas	io@wearcheckusa.cor

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCAIRCAR [WUSCAR] 06173972 (Generated: 05/12/2024 09:34:05) Rev: 1

Certificate L2367

Laboratory

Sample No. Lab Number **Unique Number** Test Package

Contact/Location: ELVIN DIAZ - UCAIRCAR

T: (800)864-7621

F: (201)342-6241